



***Innovations in Design***



Patent Pending



No instructions required. Simply turn it on and pinpoint the leak!



Rugged carrying case included

#### **KEY FEATURES**

**Superior sensitivity to R410A and new HFO refrigerants.**

**Sensor not contaminated by R404a.**

**The worlds only leak detector with fully automatic sensitivity selection and control.**

For over 30 years CPS has led the industry in portable leak detection technology and has been awarded multiple patents for it's **Innovations in Design**.

CPS® Products proudly introduces the all new **Leak-Seeker® II** featuring **E\_MOS™** technology. Packed with unique design features the new **Leak-Seeker® II** from CPS is the best leak detector you can find, anywhere in the world at any price, truly an **Innovation in Design**.

### Features:

- Microprocessor controlled sensor electronics utilizing a multi channel signal detection method, improves sensitivity while reducing false alarms.
- New **E\_MOS™** sensor technology incorporates a proprietary pulse modulation design to increase both battery and sensor life.
- Software managed sensor rejuvenation mode, automatically initiated at each startup ensures the highest level of sensitivity every use, for up to 500 hours of detecting leaks of less than .1 oz per year.
- Sensitivity remains constant over the life of the sensor.
- Dynamic signal analysis and automatic sensitivity control, enables the Leak Seeker II to make quick work of any leak regardless of its size or the refrigerant type...without operator intervention.
- The worlds only leak detector with fully automatic sensitivity selection and control.
- Senses all refrigerants including those with hydrocarbon components.
- Meets or exceeds all US and International standards for both automotive and commercial use.
- Superior sensitivity to R410A and new HFO refrigerants.
- Sensor not contaminated by R404a.
- Sensitivity to 35 parts per million (less than .1 oz per year).
- 50+ hour battery life (3 C batteries).
- 500+ hours sensor life.
- 2 year warranty.
- Patent pending.

New **E\_MOS™** sensor delivers instantaneous response to leaks.

15.5" flexible probe for hard to reach areas.

Sensitivity level indicators. Level 1 for small leaks through Level 6 for larger leaks. Leak-Seeker® II automatically determines and selects the optimum sensitivity level.

Speaker provides loud, variable frequency audible alarm indication of leak.

LED tachometer style bar graph display provides a visual indication of the leak size and enables user to home in and quickly pinpoint the exact location of leak.

Easy-one-button operation. Press to turn unit ON. Press to reset. Depress and hold to turn unit OFF. The Leak-Seeker® II does the rest.

cps



### WORLD HEADQUARTERS

1010 East 31st Street, Hialeah, Florida 33013, USA  
Tel: 305-687-4121, 1-800-277-3808, Fax: 305-687-3743  
E-mail: info@cpsproducts.com www.cpsproducts.com