


CONDENSING UNITS EUROPE

TAILORED CUSTOMIZATION



Product range suitable
for your needs.

- R134a
- R290
- R404A/R507/R452A

embraco POWER **IN.**
CHANGE **ON.**



01

ABOUT EMBRACO

02

OUR PRODUCTS

03

PRODUCTS MAP

04

NOMENCLATURE

05

TECHNICAL
INFORMATION

06

GENERAL DATA &
PERFORMANCE

07

EXTERNAL VIEWS &
WIRING DIAGRAMS

embraco POWER **IN.**
CHANGE **ON.**

EMBRACO is a company specialized in cooling solutions and world leader in the hermetic compressor market. **Our mission:** provide innovative solutions for a better quality of life, always attentive to technological excellence and sustainability.

Technological leadership, operational excellence and sustainability are some of the pillars which ensure the EMBRACO differential over other companies in the world market. Its products are now considered the favorite leading home appliance manufacturers by major automakers and are spotlighted by manufacturers of commercial refrigeration equipment.

With global operations and production capacity exceeding 38 million units a year, the company offers solutions that are differentiated for their innovation and low energy consumption. Its 11.500 employees work in factories and offices located in Brazil (headquarters), China, Italy, Slovakia, Mexico, the United States and Russia.

Energy efficiency is constantly sought in the processes, products and relationships with the communities where it operates. Our company is the absolute leader in this segment, being able to offer products that meet the most restrictive international standards regarding energy consumption.

As a worldwide leader, **EMBRACO** tries to anticipate market changes, and in doing so, our company is in a state of permanent transformation. We continuously assess our processes in order to maintain our leadership within the industry and promote growth, without forgetting the pillars of our organization.



More than 12000 employees



More than 400 professionals in R&D



Production capacity of over 37 million compressors per year



More than 500 million products produced to date



More than 1200 patents worldwide



Business conducted in more than 80 countries



R&D laboratories on 4 continents






HIGH EFFICIENCY



Energy efficiency is the base for all our product development. This means producing compressors that consume each time less energy and less raw material in manufacturing at the same time maintaining **Embraco** brand quality.


Thus, we continuously invest in research and development to create products that are more efficient and silent and do not harm the environment.




embraco

TROPICAL AND SUPERTROPICAL

All the Embraco Condensing Units are tested for tropical temperatures up to 43°C.



Available range tested for supertropical temperatures up to 48°C



EU ECODESIGN REGULATION



THE COMMISSION REGULATION (EU) DOSSIER NO 11898/14 IMPLEMENTING DIRECTIVE 2009/125/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL WITH REGARD TO **ECODESIGN REQUIREMENTS** FOR PROFESSIONAL STORAGE CABINETS, **CONDENSING UNITS** AND PROCESS CHILLERS WILL **ESTABLISH MINIMUM EFFICIENCY PERFORMANCE STANDARDS (MEPS)** FOR NEW PRODUCTS BEING PLACED ONTO THE EU MARKET AS OF JULY 1ST 2016.

The Ecodesign Directive aims to reduce the environmental impact of energy related products during their entire lifetime, it provides a framework with specific and mandatory requirements for improving product quality and environmental protection, reducing energy and resources consumption and significantly contributing to the EU's 2020 energy efficiency objective.

In addition to this, the Energy Labelling gives clear information about the energy consumption and performance of specified appliances, helping consumers and end users to select energy efficient products allowing them to make informed purchasing decisions..


The EU legislation on Ecodesign is an effective tool for eliminating the least performing products from the market. As regards to the refrigeration systems, this regulation shall apply to professional refrigerated storage cabinets and blast cabinets, condensing units operating at low and medium temperature (monoblock units or split units are excluded). If, for instance, Ecodesign requirements for domestic refrigerators do not respect the Ecodesign Directive criteria, any refrigerator which does not comply with these requirements will not be CE marked and therefore cannot be sold in the European Union.

EFFECTIVELY JULY 1ST, 2016,
THE ENTIRE EMBRACO CONDENSING UNITS RANGE
WILL MEET THE STANDARDS REQUIRED
BY THIS NEW REGULATION,
ENSURING THE CONFORMITY OF ITS PRODUCTS.

THE ECODESIGN REQUIREMENTS


The coefficient of performance (COP) and the seasonal energy performance ratio (SEPR) of the condensing units shall not drop below the values indicated in the following table:

OPERATING TEMPERATURE	RATED CAPACITY P _A	APPLICABLE RATIO	VALUE
MEDIUM	0,2 kW ≤ P _A 1 kW	COP	1,20
	1 kW ≤ P _A 5 kW	COP	1,40
	5 kW ≤ P _A 20 kW	SEPR	2,25
	20 kW ≤ P _A 50 kW	SEPR	2,35
LOW	0,1 kW ≤ P _A 0,4 kW	COP	0,75
	0,4 kW ≤ P _A 2 kW	COP	0,85
	2 kW ≤ P _A 8 kW	SEPR	1,50
	8 kW ≤ P _A 20 kW	SEPR	1,60



Note: Product data - check pages 20-22

OUR PRODUCTS



SINGLE SPEED
COMPRESSORS

EM	
EG	
F	
NE	
NT	
NTU	
NJ	

FULLMOTION INVERTER
COMPRESSORS

VEM	
VEG	
VNE	
VES	

CONDENSING UNITS

UEM	
UNE	
UNT	
UNJ	
UF	

SLIDING UNITS


STANDARD RANGE	
EXTENDED RANGE	
MULTICOMPRESSORS SOLUTION	
AVAILABLE WITH 2 OR 3 COMPRESSORS	
	

UEMT		AVAILABLE FOR:
	• Low noise • High efficiency level • Wide application range • Compact size	R134a R404A/R507/R452A R290
		APPLICATION:
		LBP, M/HBP
		COMPRESSORS FROM:
		3,4 CC TO 7,69 CC

UNE/UNEK/UNEU		AVAILABLE FOR:
	• Low noise • Low vibrations • High reliability in severe working conditions	R134a R404A/R507/R452A R290
		APPLICATION:
		LBP, M/HBP
		COMPRESSORS FROM:
		6,2 CC TO 16,8 CC

High efficiency versions of UNEK models (UNEU) available on demand

UNT		AVAILABLE FOR:
	• High efficiency level • Very low sound level • High cooling capacity at low evaporating temperatures	R134a R404A/R507/R452A
		APPLICATION:
		LBP, M/HBP
		COMPRESSORS FROM:
		14,5 CC TO 27,8 CC

UNJ		AVAILABLE FOR:
	• Small size platform • High energy efficiency • Reduced noise level	R134a R404A/R507/R452A
		APPLICATION:
		LBP, M/HBP
		COMPRESSORS FROM:
		21,7 CC TO 34,4 CC

SLIDING UNITS STANDARD RANGE		AVAILABLE FOR:
	• Low noise • High efficiency level • Wide application range • Compact size	*R134a R404A/R507/R452A
		APPLICATION:
		LBP, M/HBP
		* only LBP

SLIDING UNITS EXTENDED RANGE		AVAILABLE FOR:
	• Low noise • High efficiency level • Wide application range • Compact size	*R134a R404A/R507/R452A
		APPLICATION:
		LBP, M/HBP
		* only LBP

MULTICOMPRESSORS

A new entry into Embraco's Condensing Units: Multicompressors architecture is the smart solution to have small size platform, high efficiency and reduced noise level.



MULTICOMPRESSORS SOLUTION
• Small size platform
• High energy efficiency
• Reduced noise level
AVAILABLE FOR: R134a, R404A/R507/R452A
APPLICATION: LBP, M/HBP
COMPRESSORS FROM: 21,7 CC TO 34,4 CC

PRODUCT FEATURES
extended range up to 8,5kW
available for R134a, R404A
2 or 3 compressor units
compact size
lower energy consumption
power control: possibility to switch on or switch off compressors based on required cooling capacity
doublestage delay unit (timer)
gradually switching of high loads
IoT control elements

PRODUCT MAP
50 - 60 HZ





CONDENSING UNIT PRODUCT MAP • 50 Hz

	R134a													R404A / R507 / R452A													R290																																																	
	LBP	VOLT. FREQ.	AMB. [°C]	COOL. CAP. (-35°C) [W]	POWER INPUT [W]	COP [W/W]	DISPL. [CC]	M/HBP	VOLT. FREQ.	AMB. [°C]	COOL. CAP. (-10°C) [W]	POWER INPUT [W]	COP [W/W]	DISPL. [CC]	LBP	VOLT. FREQ.	AMB. [°C]	COOL. CAP. (-35°C) [W]	POWER INPUT [W]	COP [W/W]	DISPL. [CC]		M/HBP	VOLT. FREQ.	AMB. [°C]	COOL. CAP. (-10°C) [W]	POWER INPUT [W]	COP [W/W]	DISPL. [CC]	LBP	VOLT. FREQ.	AMB. [°C]	COOL. CAP. (-35°C) [W]	POWER INPUT [W]	COP [W/W]	DISPL. [CC]	MBP	VOLT. FREQ.	AMB. [°C]	COOL. CAP. (-10°C) [W]	POWER INPUT [W]	COP [W/W]	DISPL. [CC]																																	
UEMT	UEMT49HLP	A	25	102	107	0,96	5,57	UEMT37HDP	A	25	224	126	1,78	3,40	UEMT2117GK	A	25	160	140	1,14	4,50	UEMT6144GK	A	25	424	215	1,97	3,97	UEMT2121U	A	25	176	164	1,07	5,57	UEMT6144U	A	25	440	182	2,42	4,50																																		
			32	93	110	0,85				32	204	130	1,57				32	145	144	1,01				32	385	222	1,73				32	160	169	0,95				32	400	188	2,13																																			
			43	74	117	0,64				43	163	138	1,18				43	116	153	0,76				43	308	235	1,31				43	128	179	0,71				43	320	199	1,61																																			
								UEMT45HDR	A	25	253	138	1,84	3,97	UEMT2121GK	A	25	201	170	1,19	5,20	UEMT6152GK	A	25	435	218	1,99	4,50	UEMT2125U	A	25	190	177	1,08	5,96	UEMT6152U	A	25	510	202	2,53	5,20																																		
										32	230	142	1,62				32	183	175	1,05				32	395	225	1,76				32	173	182	0,95				32	464	208	2,23																																			
										43	184	151	1,22				43	159	170	0,94				43	316	239	1,33				43	138	193	0,72				43	371	220	1,68																																			
								UEMT50HDP	A	25	287	147	1,95	4,50	UEMT2125GK	A	25	228	207	1,10	5,96	UEMT6165GK	A	25	524	258	2,03	5,20											UEMT6165U	A	25	539	243	2,21	5,96																															
										32	261	152	1,72				32	203	213	0,95				32	477	266	1,79														32	490	251	1,95																																
										43	209	161	1,30				43	160	217	0,74				43	381	282	1,35														43	392	266	1,47																																
								UEMT6144Z	A	25	308	171	1,80	5,20	UEMT2130GK	A	25	263	233	1,13	6,76																																																							
										32	280	176	1,59				32	239	240	1,00																																																								
										43	224	187	1,20				43	191	254	0,75																																																								
							UEMT6160Z	A	25	410	221	1,86	6,76																																																															
									32	373	228	1,64																																																																
									43	298	242	1,23																																																																
							UEMT6170Z	A	25	461	255	1,81	7,69																																																															
									32	432	261	1,66																																																																
									43	351	273	1,29																																																																
UNE	UNEK1116Z	A	25	99	115	0,86	7,40	UNEK6160Z	A	25	408	230	1,78	7,28	UNEK2125GK	A	25	204	199	1,02	6,20	UNEK6165GK	A	25	550	309	1,78	6,20	UNEK2121U	A	25	157	148	1,06	6,20	UNEK6181U	A	25	560	293	1,91	7,28																																		
			32	90	119	0,76				32	371	237	1,57				32	185	205	0,90				32	500	319	1,57				32	143	153	0,93				32	509	302	1,69																																			
			43	72	126	0,57				43	297	251	1,18				43	148	217	0,68				43	400	338	1,18				43	114	162	0,71				43	407	320	1,27																																			
	UNEK1118Z	A	25	111	129	0,86	8,40	UNEK6170Z	A	25	461	251	1,83	8,40	UNEK2134GK	A	25	238	222	1,07	7,28	UNEK6181GK	A	25	643	383	1,68	7,28	UNEK2125U	A	25	223	199	1,12	7,28	UNEK6210U	A	25	730	366	2,00	8,78																																		
			32	101	133	0,76				32	419	259	1,62				32	216	229	0,94				32	585	395	1,48				32	203	205	0,99				32	664	377	1,76																																			
			43	81	141	0,57				43	335	275	1,22				43	173	243	0,71				43	468	419	1,12				43	162	217	0,75				43	531	400	1,33																																			
	UNEK2116Z	A	25	114	131	0,87	7,40	UNEK6187Z	A	25	502	299	1,68	10,00	UNEK2150GK	A	25	354	330	1,07	8,78	UNEK6210GK	A	25	821	459	1,79	8,78	UNEK2134U	A	25	317	276	1,15	10,00	UNEK6213U	A	25	815	497	1,64	12,12																																		
			32	104	135	0,77				32	457	308	1,48				32	322	340	0,95				32	731	489	1,49				32	288	285	1,01				32	741	512	1,45																																			
			43	83	143	0,58				43	365	326	1,12				43	258	360	0,71				43	573	530	1,08				43	230	302	0,76				43	593	543	1,09																																			
	UNE2121Z	A	25	135	157	0,86	9,27	UNEK6210Z	A	25	639	379	1,69	12,12	UNEK2168GK	A	25	403	372	1,08	14,30	UNEK6213GK	A (CSIR)	25	1063	615	1,73	12,12	UNEK2150U	A	25	365	333	1,10	13,54	UNEK6210U	A	25	755	362	2,09	8,78																																		
			32	123	162	0,76				32	581	391	1,49				32	367	384	0,95				32	966	634	1,52				32	332	343	0,97				32	686	373	1,84																																			
			43	98	172	0,57				43	465	414	1,12				43	293	407	0,72				43	773	672	1,15				43	266	364	0,73				43	549	395	1,39																																			
UNE2130Z	A	25	207	195	1,06	12,12	UNEK6212Z	A (CSIR)	25	730	433	1,69	14,30	UNE2168GK	A	25	473	446	1,06	14,30	UNEK6217GK	A	25	1326	712	1,86	14,30	UNEK2160U	A	25	446	372	1,20	16,80	UNEK6217U	A	25	1245	562	2,22	14,30																																			
		32	188	201	0,94				32	664	446	1,49				32	430	460	0,93				32	1205	734	1,64				32	405	383	1,06				32	1132	579	1,96																																				
		43	136	197	0,69				43	531	473	1,12				43	344	488	0,71				43	964	778	1,24				43	324	406	0,80				43	906	614	1,48																																				
UNE2134Z	A	25	226	210	1,08	14,30	UNEK6214Z	A	25	838	514	1,63	16,80																																																															
		32	205	216	0,95				32	762	530	1,44																																32	675	416	1,62	32	471	405	1,16	32	471	405	1,16	32	471	405	1,16																	
		43	164	229	0,72				43	610	562	1,09																																43	540	441	1,22	43	377	429	0,88	43	377	429	0,88	43	377	429	0,88																	
UNEK2140Z	A	25	238	254	0,93	16,80	UNEK6210Z	A	25	703	382	1,84	12,12																																																															
		32	216	262	0,82				32	639	394	1,62																																		32	675	416	1,62	32	471	405	1,16	32	471	405	1,16	32	471	405	1,16															
		43	173	278	0,62				43	511	418	1,22																																		43	540	441	1,22	43	377	429	0,88	43	377	429	0,88	43	377	429	0,88															
UNT								UNT6215Z	N	25	946	493	1,92	17,40	UNT2168GK	N	25	403	364	1,11	14,50	UNT6217GK	A	25	1169	611	1,91	12,55	UNT2170U	A	25	590	451	1,31	20,40	UNT6217U	A	25	903	530	1,71	14,50																																		
										32	860	508	1,69				32	367	375	0,98				32	1063	630	1,69				32	536	465	1,15				32	821	546	1,50																																			
										43	688	538	1,28				43	293	398	0,74				43	850	668	1,27				43	429	493	0,87				43	657	579	1,13																																			
								UNT6217Z	A	25	1048	597	1,76	20,40	UNT2178GK	A	25	498	444	1,12	17,40	UNT6220GK	N	25	1396	694	2,01	14,50	UNT2180U	A	25	620	490	1,27	22,40	UNT6220U	A	25	1283	636	2,02	17,40																																		
										32	953	615	1,55				32	453	458	0,99				32	1269	715	1,77				32	564	505	1,12				32	1166	656	1,78																																			
										43	762	652	1,17				43	362	485	0,75				43	1015	758	1,34				43	451	535	0,84				43	933	695	1,34																																			
								UNT6220Z	N	25	1263	618	2,04	22,40	UNT2180GK	A	25	564	519	1,09	20,40	UNT6222GK	A	25	1615	841	1,92	17,40	UNT2210U	A	25	792	666	1,19	27,80	UNT6222U	A	25	1538	816	1,88	20,40																																		
										32	1148	637	1,80				32	513	535	0,96				32	1468	867	1,69				32	1468	867	1,69				32	1388	837	1,66																																			
										43	918	675	1,36				43	410	567	0,72				43	1174	919	1,28				43	576	728	0,79				43	1116	912	1,22																																			
								UNTU6224Z	A	25	1602	757	2,12	28,80	UNT2192GK	A	25	576	564	1,02	22,40	UNT6224GK	A	25	1800	916	1,97	20,40																																																




CONDENSING UNIT PRODUCT MAP • 50 Hz

	R134a							R404A / R507 / R452A																													
	M/HBP	VOLT. FREQ.	AMB. [°C]	COOL. CAP. (-10°C) [W]	POWER INPUT [W]	COP [W/W]	DISPL. [CC]	LBP	VOLT. FREQ.	AMB. [°C]	COOL. CAP. (-35°C) [W]	POWER INPUT [W]	COP [W/W]	DISPL. [CC]	M/HBP	VOLT. FREQ.	AMB. [°C]	COOL. CAP. (-10°C) [W]	POWER INPUT [W]	COP [W/W]	DISPL. [CC]																
UGNT/UGNJ GEMINI UNITS	UGNJ6220ZX	M	25	2279	1258	1,81	2X26,10	UGNT2180GK	A	25	1086	982	1,11	2X20,40	UGNJ9226GK	V	25	3359	1775	1,89	2X21,70																
			32	2072	1297	1,60				32	987	1012	0,98				32	3053	1830	1,67																	
			43	1657	1375	1,21				43	790	1073	0,74				43	2443	1940	1,26																	
	UGNJ6226ZX	M	25	3059	1727	1,77	2X34,40	UGNJ2192GK	A	25	1089	1033	1,05	2X26,10	UGNJ9226GS	M	25	3306	2052	1,61	2X21,70																
			32	2781	1780	1,56				32	990	1065	0,93				32	3005	2115	1,42																	
			43	2225	1887	1,18				43	792	1129	0,70				43	2404	2242	1,07																	
							UGNJ2192GS	M	25	1089	1055	1,03	2X26,10	UGNJ9232GK	A	25	3838	2423	1,58	2X26,10																	
									32	990	1088	0,91				32	3489	2498	1,40																		
									43	792	1153	0,69				43	2791	2648	1,05																		
							UGNJ2212GK	A	25	1576	1451	1,09	2X34,40	UGNJ9232GS	M	25	4026	2386	1,69	2X26,10																	
									32	1433	1496	0,96				32	3660	2460	1,49																		
									43	1146	1586	0,72				43	2928	2608	1,12																		
						UGNJ2212GS	M	25	1799	1607	1,12	2X34,40	UGNJ9238GK	V	25	5469	3432	1,59	2X32,70																		
								32	1635	1657	0,99				32	4972	3538	1,41																			
								43	1302	1631	0,80				43	3978	3750	1,06																			
																						25	4986	2954	1,69	25	4986	2954	1,69								
																						32	4533	3045	1,49	32	4533	3045	1,49								
																						43	3626	3228	1,12	43	3626	3228	1,12								
SUPERTROPICAL								USNJ2192GK	A	25	816	761	1,07	26,10	USEMT6165GK	A	25	583	296	1,97	5,20																
										32	742	785	0,95				32	530	305	1,74																	
										43	594	832	0,71				43	424	323	1,31																	
								USNJ2212GK	A	25	868	809	1,07	34,40	USNEK6210GK	A	25	871	435	2,00	8,78																
										32	789	834	0,95				32	792	448	1,77																	
										43	631	884	0,71				43	634	475	1,33																	
																													25	1139	655	1,74	25	1139	655	1,74	
																													32	1035	675	1,53	32	1035	675	1,53	
																														43	828	716	1,16	43	828	716	1,16
																														25	2064	1038	1,99	25	2064	1038	1,99
																						32	1876	1070	1,75	32	1876	1070	1,75								
																						43	1501	1134	1,32	43	1501	1134	1,32								
																						25	2427	1244	1,95	25	2427	1244	1,95								
																						32	2206	1282	1,72	32	2206	1282	1,72								
																						43	1765	1359	1,30	43	1765	1359	1,30								
																						25	2835	1562	1,82	25	2835	1562	1,82								
																						32	2577	1610	1,60	32	2577	1610	1,60								
																						43	2062	1707	1,21	43	2062	1707	1,21								
																						25	2935	1428	2,06	25	2935	1428	2,06								
																						32	2668	1472	1,81	32	2668	1472	1,81								
																						43	2134	1560	1,37	43	2134	1560	1,37								
SLIDING UNITS	UDNEK6187Z	A	25	AVAILABLE ON DEMAND				UDNEK2134GK		25	AVAILABLE ON DEMAND				UDNEK6210GK	A	25	774	452	1,71	8,78																
			32	AVAILABLE ON DEMAND						32	AVAILABLE ON DEMAND						32	704	466	1,51																	
			43	AVAILABLE ON DEMAND						43	AVAILABLE ON DEMAND						43	563	494	1,14																	
	UDNEK6210Z	A	25	657	353	1,86	12,12	UDNEK2150GK	A	25	351	374	0,94	12,12	UDNEK6213GK	A	25	998	640	1,56	12,12																
			32	597	364	1,64				32	319	386	0,83				32	907	660	1,37																	
			43	478	386	1,24				43	255	409	0,62				43	726	700	1,04																	
	UDNEK6212Z	A	25	728	425	1,71	14,30	UDNEK2168GK	A	25	425	431	0,99	14,30	UDNEK6217GK	A	25	1302	682	1,91	14,30																
			32	662	438	1,51				32	386	444	0,87				32	1184	703	1,68																	
			43	530	464	1,14				43	309	471	0,66				43	947	745	1,27																	
	UDNEK6214Z	A	25	834	526	1,59	16,80	UDNEK2178GK	A	25	AVAILABLE ON DEMAND				UDNT6220GK	A	25	AVAILABLE ON DEMAND																			
			32	758	542	1,40				32	AVAILABLE ON DEMAND						32	AVAILABLE ON DEMAND																			
			43	606	575	1,06				43	AVAILABLE ON DEMAND						43	AVAILABLE ON DEMAND																			
	UDNT6215Z	N	25	902	465	1,94	17,40	UDNT2180GK	A	25	592	558	1,06	20,40	UDNT6222GK	A	25	1445	801	1,80	17,40																
			32	820	479	1,71				32	538	575	0,94				32	1314	826	1,59																	
			43	656	508	1,29				43	430	610	0,71				43	1051	876	1,20																	
	UDNT6217Z	A	25	1052	597	1,76	20,40	UDNT2192GK	A	25	657	545	1,21	22,40	UDNT6226GK	A	25	1775	1044	1,70	22,40																
			32	956	615	1,55				32	607	553	1,10				32	1614	1076	1,50																	
			43	765	652	1,17				43	487	558	0,87				43	1291	1141	1,13																	
	UDNT6220Z	A	25	AVAILABLE ON DEMAND				UDNT2212GK	A	25	798	689	1,16	27,80	UDNJ9232GK	A	25	2261	1244	1,82	26,10																
			32	AVAILABLE ON DEMAND						32	725	710	1,02				32	2055	1282	1,60																	
			43	AVAILABLE ON DEMAND						43	580	753	0,77				43	1644	1359	1,21																	
	UDNJ6220Z	A	25	1349	716	1,88	26,10	UDNJ2192GS	M	25	AVAILABLE ON DEMAND				UDNJ9238GK	V	25	2664	1610	1,65	32,70																
			32	1226	738	1,66				32	AVAILABLE ON DEMAND						32	2422	1660	1,46																	
			43	981	782	1,25				43	AVAILABLE ON DEMAND						43	1938	1760	1,10																	
	UDNJ6220ZX	M	25	AVAILABLE ON DEMAND				UDNJ2212GS	M	25	AVAILABLE ON DEMAND				UDNJ9226GS	M	25	AVAILABLE ON DEMAND																			
			32	AVAILABLE ON DEMAND						32	AVAILABLE ON DEMAND						32	AVAILABLE ON DEMAND																			
			43	AVAILABLE ON DEMAND						43	AVAILABLE ON DEMAND						43	AVAILABLE ON DEMAND																			
	UDNJ6226Z	A	25	1673	882	1,90	34,40	UDNJ2212GK	A	25	934	823	1,14	34,40	UDNJ9232GS	M	25	AVAILABLE ON DEMAND																			
			32	1521	901	1,69				32	849	848	1,00				32	AVAILABLE ON DEMAND																			
			43	1264	922	1,37				43	679	899	0,76				43	AVAILABLE ON DEMAND																			
	UDNJ6226ZX	M	25	AVAILABLE ON DEMAND				UDNJ2192GS	M	25	AVAILABLE ON DEMAND				UDNJ9238GS	M	25	AVAILABLE ON DEMAND																			
			32	AVAILABLE ON DEMAND						32	AVAILABLE ON DEMAND						32	AVAILABLE ON DEMAND																			
43			AVAILABLE ON DEMAND							43	AVAILABLE ON DEMAND						43	AVAILABLE ON DEMAND																			
								UDNJ2212GS	M	25	AVAILABLE ON DEMAND				UDH79B26UABHA	A	25	4043	2142	1,89	48,00																
										32	AVAILABLE ON DEMAND						32	AVAILABLE ON DEMAND						32	3675	2208	1,66										
										43	AVAILABLE ON DEMAND						43	AVAILABLE ON DEMAND						43	2940	2340	1,26										
																						25	1042	791	1,32	25	5148	2350	2,19								
																						32	947	815	1,16	32	4680	2423	1,93								
																						43	758	864	0,88	43	3744	2568	1,46								
																						25	1515	1148	1,32	25	7192	2289	3,14								
																						32	1377	1183	1,16	32	6538	2360	2,77								
																						43	1102	1254	0,88	43	5230	2502	2,09								
																						25	2154	1693	1,27	25	8664	4001	2,17								
																						32	1958	1745	1,12	32	7876	4125	1,91								
																						43	1566	1850	0,85	43	6301	4373	1,44								
																						25	10033	4745	2,11	25	10033	4745	2,11								
																						32	9121	4892	1,86	32	9121	4892	1,86								
																						43	7297	5186	1,41	43	7297	5186	1,41								


NOMENCLATURE



MODEL DESCRIPTION CONDENSING UNIT SERIES:
UEMT/UNE/UNJ/UNT/UDH/UDL



CONDENSING UNIT BILL OF MATERIAL CODE







TECHNICAL INFORMATION



OPERATING ENVELOPE





R134a

Note: usage of condensing unit outside the intended working range cannot make use of the warranty, or should be consulted with Technical support.



R404A
R507
R452A
R290

Note: usage of condensing unit outside the intended working range cannot make use of the warranty, or should be consulted with Technical support.



APPLICATIONS

LBP	LOW BACK PRESSURE	APPLICATIONS:
	Evaporating temperature lower than -20° C	refrigerators,frozen food cabines, frozen food display cases, display windows, etc.
MBP	MEDIUM BACK PRESSURE	APPLICATIONS:
	Evaporating temperature between -20° C and 0° C	fresh food cabinets, drink coolers, ice makers, etc.
M/HBP	MEDIUM / HIGH BACK PRESSURE	APPLICATIONS:
	Evaporating Temperature between -20° C and +10° C	coolers, merchandisers, etc.
HBP	HIGH BACK PRESSURE	APPLICATIONS:
	High evaporating temperatures between -15° C and +10°C	fresh food cabinets, bottle coolers,dehumidifiers, etc.

TEST CONDITIONS

TEST CONDITIONS	APPLICATION	EVAPORATING TEMPERATURE °C	GAS RETURN TEMPERATURE °C	SUB-COOLING K	COMPRESSOR AMBIENT TEMPERATURE °C
EN 13215	LBP	-35	20	3K	32
	M and HBP	-10	20	3K	32
ASHRAE	LBP	-23,3	32	3K	32
	M and HBP	7,2	32	3K	32

EXPANSION DEVICE

C	Capillary Tube.
V	Expansion Valve.

MOTOR TORQUE

LST	(Low Starting Torque) Compressor with RSIR - RSCR - PSC electrical motor for sysyems with capillarity tube and with equalized pressures at start up.
HST	(High Starting Torque) Compressor with CSIR - CSR and 3ph electrical motor for sysyems with capillarity equalized or not equalized pressures at start up.

ELECTRICAL MOTOR TYPES

RSIR	Resistance Start – Inductive Run This motor type , used in the compressor of small power, has a low starting torque (LST) and must be applied only to capillary tube systems where the pressures equalize. The motor is characterized by a start winding with high ohmic resistance and must be disconnected when it reaches the stabilized rotational speed. An electromagnetic relay, calibrated for the motor current, disconnects the start winding at the end of the start up. An alternative to the electromagnetic relay is, for some models, a PTC solid state-starting device.
RSCR	Resistance Start – Capacitive Run Similar to RSIR motor version but uses a PTC solid state starting device and a permanent connected run capacitor to improve its efficiency.
CSIR	Capacitive Start – Inductive Run Similar to RSIR motor, with a different start winding in series with a start capacitor of suitable capacitance to get a high starting torque.
CSR	Capacitive Start & Run CSR version with capacitive run and start windings. Same as PSC motor but with a start capacitor in series with the start winding. A potential starting relay, calibrated for each motor, disconnects the start capacitor at the end of the start. The motor is characterized by a high starting torque (HST) and high efficiency.
PSC	Permanent Split Capacitor: PSC version with capacitive run winding. This motor is characterized by the run capacitor permanently connected in series with the start winding; both remain connected even after the motor starts. The starting torque is enough to guarantee that the compressor starts only with balanced pressures in capillary tubes systems or with a pressure equalizer.
3Ø	Three Phase Three-phase windings with star connections.

ELECTRICAL COMPONENTS

TYPE OF MOTOR	Overload Protector (*)	STARTING DEVICE				CAPACITOR	
		Current Relay	Voltage Relay	PTC	TSD	Start	Run
RSIR	✓	✓	X	✓	X	X	X
RSCR	✓	X	X	✓	✓	X	✓
CSIR	✓	✓	X	X	X	✓	X
CSR	✓	X	✓	X	X	✓	✓
PSC	✓	X	X	X	X	X	✓
3-Phases	✓	X	X	X	X	X	X


* Optional

VOLTAGE & FREQUENCY

Code	Voltage & Frequency	Voltage Working Range		Minum Start Voltage	
		50Hz	60Hz	50Hz	60Hz
A	220 - 240V 50Hz 1 ~	198V - 254V		187V	
B	200 - 230V 50Hz / 208 - 230V 60Hz 1 ~	180V - 244V	187V - 244V	170V	177V
C	220V 50Hz 1 ~	200V - 242V		187V	
D	208 - 230V 60Hz 1 ~		187V - 244V		177V
E	115 - 127V 60Hz 1 ~		103V - 134V		98V
F	100V 50 Hz / 100 - 127V 60Hz 1 ~	90V - 110V	90V - 134V	85V	85V
G	115V 60Hz 1 ~		103V - 127V		98V
J	230V 60Hz 1 ~		207V - 253V		195V
K	200 - 220 V 50 Hz / 230 V 60 Hz 1~	180V - 234V	207V - 253V	170V	195V
M	380 - 420V 50Hz / 440 - 480V 60 Hz 3 ~	332V - 445V		323V	
N	200 - 240V 50Hz / 230V/60Hz 1 ~	180V - 254V	207V -253V	170V	195V
P	380V 60Hz 3 ~		342V -418V		323V
Q	100V 50 / 60 Hz 1~	90V - 110V	90V -110V	85V	85V
R	200V 50 / 60Hz 3 ~	180V - 220V	180V - 220V	170V	170V
V	230V 50Hz 1 ~	207V - 253V		195V	
X	220 - 240V 50 / 60 Hz 1 ~	150V (160V*) - 240V		150V (160V*)	
Z	200 - 230V 60Hz 1 ~		180V - 244V		170V


* Depending on compressor family, for details contact Technical Support.

ACCESSORIES & EXECUTION
NAKED UNIT



MAIN PARTS	A - Compressor / B - Condenser & Fan Mmotor
OPTIONAL PARTS	C - Receiver / D - Pressure switch / E - Valves / F - Filter drier / G - Sight glass / H - Electrical box / I - Fan speed control


ACCESSORIES & EXECUTION
SLIDING UNIT




MAIN PARTS	A - Compressor / B - Condenser & Fan Motor
OPTIONAL PARTS	C - Receiver / D - Pressure switch / E - Valves / F - Filter drier / G - Sight glass / H - Electrical box / I - Fan speed control / J - Connect line to the top of unit

CONDENSING UNIT EXECUTIONS


w/o receiver - w/o valves




w/o receiver -
schrader valve




w/o receiver - schrader valve -
valves (flare or solder)



receiver - schrader valve -
valves (flare or solder)



receiver - schrader valve -
valves (flare or solder) -
pressure switch



receiver - schrader valve -
valves (flare or solder) -
pressure switch - liquid line





PACKAGING

CDU	QUANTITY PER PALLET
UEM	24
UNE	from 12 to 24
UNT	from 8 to 21
UNJ	from 4 to 12
UGN	4
SLIDING UNITS	1

IDENTIFICATION LABEL

UEM/UNE/UNT/UNJ/UGN/SLIDING UNITS



- 1

Condensing unit model
- 2

Condensing unit bill of material
- 3

Voltage
- 4

Frequency
- 5

Phases
- 6

Full load amperage
- 7

Locked rotor amperage
- 8

Fan output
- 9

Cooling capacity at rated point

10

Refrigerant

11

Receiver volume

12

Application type

13

Maximum pressure at high side

14

Maximum pressure at low side

15

Agency approvals

16

Date of production code

17

serial No.

GENERAL DATA & PERFORMANCE



R134a • LBP • 50Hz

							PERFORMANCE DATA ASHRAE				PERFORMANCE DATA EN13215																									
SERIES	MODEL	VOLTAGE & FREQUENCY CODE	MOTOR TYPE	DISPL. cm³	LRA A	HP	EVAPORATING TEMPERATURE °C															RECEIVER VOLUME liter	VALVE CONNECTION EXT. DIAMETER		FAN				WEIGHT (REF. ONLY) kg	OVERALL DIMENSIONS				CONDENSER		MODEL
							RATED POINT -23,3 °C				RATED POINT -35 °C			W	W	W	W	W	W	SUCTON inch			LIQUID inch	EXTERNAL DIAMETER mm	No. / ANGLE OF BLADES	No. OF FANS	AIR FLOW RATE m³/h	A mm		B mm	C mm	EXT. VIEW REF.	No. OF ROWS	No. OF TUBES		
							COOLING W	POWER INPUT W	CURRENT A	EFFICIENCY W/W	COOLING W	POWER INPUT W	EFFICIENCY W/W																							
UEMT	UEMT49HLP	A	RSIR	5,57	5,2	1/5	150	115	1,02	1,30	93	110	0,85	115	142	183	228	283	341		-	3/8	1/4	200	5/28°	1	360	14,0	430	306	226	DWG01	2	8	UEMT49HLP	
UNE	UNE2121Z	A	CSIR	9,27	12,6	1/3	308	269	2,00	1,14	123	162	0,76	188	263	349	451	566	692		0,6	3/8	1/4	200	5/28°	1	300	17,2	430	306	226	DWG05	3	8	UNE2121Z	
	UNE2130Z	A	CSIR	12,12	13,2	1/3	322	279	2,15	1,15	188	201	0,94	231	289	361	448	549	664		1,1	3/8	1/4	230	5/28°	1	300	16,5	435	308	254	DWG05	3	9	UNE2130Z	
	UNE2134Z	A	CSIR	14,30	17,0	1/2	387	285	2,25	1,36	205	216	0,95	242	304	392	490	609	733		1,1	3/8	1/4	254	5/28°	1	595	20,0	465	340	296	DWG08	3	11	UNE2134Z	
	UNEK1116Z	A	RSIR	7,40	5,3	1/4	203	182	1,07	1,12	90	119	0,76	112	151	201	260	331	406		-	3/8	1/4	200	5/28°	1	360	14,9	430	306	226	DWG05	2	8	UNEK1116Z	
																													480	300	226	DWG07				
	UNEK1118Z	A	RSIR	8,40	6,9	1/3	244	185	1,19	1,32	101	133	0,76	141	188	251	330	420	522		-	3/8	1/4	200	5/28°	1	360	15,3	430	306	226	DWG05	2	8	UNEK1118Z	
																													480	300	226	DWG07				
	UNEK2116Z	A	CSIR	7,40	10,0	1/4	197	191	1,37	1,03	104	135	0,77	124	155	200	265	341	439		-	3/8	1/4	200	5/28°	1	360	16,5	430	306	226	DWG05	2	8	UNEK2116Z	
UNEK2140Z	A	CSIR	16,80	19,0	1/2+	UD	UD	UD	UD	216	262	0,82	298	388	505	640	785	944		1,1	3/8	1/4	254	5/28°	1	595	20,0	465	340	296	DWG08	3	11	UNEK2140Z		

Note:
Expansion device C/V
Expansion device C: UEMT49HLP, UNEK1116Z, UNEK1118Z, UNEK2116Z
UD - Under Development
High efficiency versions of UNEK models (UNEU) available on demand

R134a • HBP • 50Hz

							PERFORMANCE DATA ASHRAE				PERFORMANCE DATA EN13215																							
SERIES	MODEL	VOLTAGE & FREQUENCY CODE	MOTOR TYPE	DISPL. cm³	LRA A	HP	EVAPORATING TEMPERATURE °C													RECEIVER VOLUME liter	VALVE CONNECTION EXT. DIAMETER		FAN				WEIGHT (REFERENCE ONLY) kg	OVERALL DIMENSIONS				CONDENSER		MODEL
							RATED POINT 7,2 °C				-15	RATED POINT -10 °C			-5	0	5	10			SUCTION INCH	LIQUID INCH	EXTERNAL DIAMETER mm	NO. / ANGLE OF BLADES	NO. OF FANS	AIR FLOW RATE m³/h		A mm	B mm	C mm	EXT. VIEW REF.	NO. OF ROWS	NO. OF TUBES	
							COOLING W	POWER INPUT W	CURRENT A	EFFICIENCY W/W	W	COOLING W	POWER INPUT W	EFFICIENCY W/W	W	W	W	W																
UEMT	UEMT37HDP	A	RSIR	3,40	5,4	1/8	UD	UD	UD	UD	166	204	130	1,57	251	310	362	429	-	3/8	1/4	200	5/28°	1	300	13,5	430	308	226	DWG02	3	8	UEMT37HDP	
	UEMT45HDR	A	CSIR	3,97	8,8	1/7	447	185	1,26	2,42	185	230	142	1,62	277	335	399	474	-	3/8	1/4	200	5/28°	1	300	13,8	430	308	226	DWG02	3	8	UEMT45HDR	
	UEMT50HDP	A	RSIR	4,50	9,1	1/6	UD	UD	UD	UD	208	261	152	1,72	324	390	463	556	0,6	3/8	1/4	200	5/28°	1	300	13,8	430	308	226	DWG02	3	8	UEMT50HDP	
	UEMT6144Z	A	CSIR	5,20	8,5	1/5	573	235	1,48	2,44	221	280	176	1,59	349	431	523	625	0,6	3/8	1/4	200	5/28°	1	300	15,2	430	308	226	DWG02	3	8	UEMT6144Z	
	UEMT6160Z	A	CSIR	6,76	9,8	1/4	758	314	1,87	2,41	297	373	228	1,64	465	550	630	750	1,1	3/8	1/4	230	5/28°	1	420	15,5	435	308	254	DWG03	3	9	UEMT6160Z	
	UEMT6170Z	A	CSIR	7,69	10,4	1/3	757	381	2,24	1,99	352	432	261	1,66	520	617	722	836	1,1	3/8	1/4	230	5/28°	1	420	15,5	435	308	254	DWG03	3	9	UEMT6170Z	
UNE	UNEK6160Z	A	CSIR	7,28	11,5	1/4	753	306	2,10	2,46	295	371	237	1,57	457	553	660	777	1,1	3/8	1/4	230	5/31°	1	420	18,9	435	305	254	DWG05	3	9	UNEK6160Z	
	UNEK6170Z	A	CSIR	8,40	12,4	1/4	836	348	2,25	2,40	336	419	259	1,62	514	619	735	862	1,1	3/8	1/4	230	5/31°	1	420	19,3	435	305	254	DWG05	3	9	UNEK6170Z	
	UNEK6187Z	A	CSIR	10,00	16,1	1/3	958	418	2,86	2,29	359	457	308	1,48	574	711	870	1043	1,1	3/8	1/4	254	5/28°	1	320	21,0	465	340	296	DWG08	3	11	UNEK6187Z	
																										465	340	296	DWG06					
	UNEK6210Z	A	CSIR	12,12	19,5	1/3+	1228	497	2,90	2,47	466	581	391	1,49	704	835	975	1123	1,1	3/8	1/4	254	5/28°	1	595	21,7	465	340	296	DWG08	3	11	UNEK6210Z	
																											465	340	296	DWG06				
	UNEK6212Z	A	CSIR	14,30	19,5	1/2+	1448	730	3,95	1,98	539	664	446	1,49	807	969	1149	1348	1,1	3/8	1/4	254	5/28°	1	595	21,5	465	340	296	DWG08	3	11	UNEK6212Z	
																											465	340	296	DWG06				
	UNEK6212Z	B	CSR	14,30	22,5	1/2+	1456	698	3,86	2,09	517	637	426	1,50	795	1001	1205	1421	1,0	3/8	1/4	254	5/28°	1	660	21,7	465	340	296	DWG08	3	11	UNEK6212Z	
UNEK6214Z	A	CSIR	16,80	25,5	1/2+	1492	753	5,17	1,98	619	762	530	1,44	923	1100	1294	1505	1,0	3/8	1/4	254	5/28°	1	595	21,7	465	340	296	DWG08	3	11	UNEK6214Z		
																										465	340	296	DWG06					
UNT	UNT6215Z	A	CSIR	12,12	19,5	1/3+	1253	554	3,49	2,26	509	639	394	1,62	782	937	1105	1285	1,1	3/8	1/4	254	5/28°	1	595	21,7	465	340	296	DWG08	3	11	UNEU6210Z	
																										465	340	296	DWG06					
	UNT6215Z	N	CSIR	17,40	21,0	1/2+	1483	593	5,52	2,50	682	860	508	1,69	1056	1272	1507	1761	1,2	3/8	1/4	254	5/28°	1	740	28,2	465	340	296	DWG14	3	11	UNT6215Z	
	UNT6217Z	A	CSR	20,40	25,0	3/4	1781	745	5,65	2,39	773	953	615	1,55	1171	1426	1718	2048	2,3	1/2	3/8	275	5/31°	1	640	30,0	470	395	324	DWG15	3	12	UNT6217Z	
UNJ	UNT6220Z	N	CSIR	22,40	29,0	3/4	1970	960	5,99	2,05	910	1148	637	1,80	1413	1704	2020	2364	2,3	1/2	3/8	275	5/31°	1	640	33,5	470	395	324	DWG19	3	12	UNT6220Z	
	UNTU6224Z	A	CSR	27,80	UD	UD	UD	UD	UD	UD	1247	1456	780	1,87	1834	2213	2588	3095	2,3	1/2	3/8	275	5/31°	1	640	UD	UD	UD	UD	UD	3	12	UNTU6224Z	
	UNJ6220Z	A	CSR	26,10	35,0	4/5	2338	1080	6,79	2,16	989	1254	765	1,64	1547	1868	2216	2592	2,3	1/2	3/8	275	5/31°	1	640	36,9	481	409	324	DWG27	3	12	UNJ6220Z	
	UNJ6220ZX	M	3 PH	26,10	10,0	4/5	2285	1004	2,28	2,28	1015	1259	724	1,74	1534	1838	2210	2538	2,3	1/2	3/8	275	5/31°	1	640	35,4	481	409	324	DWG28	3	12	UNJ6220ZX	
UNJ	UNJ6226Z	A	CSR	34,40	31,0	1+	3006	1355	6,75	2,22	1217	1531	987	1,55	1896	2312	2759	3244	2,3	5/8	3/8	275	5/31°	1	640	37,5	481	409	324	DWG27	3	12	UNJ6226Z	
	UNJ6226ZX	M	3 PH	34,40	13,0	1	2796	1293	2,40	2,16	1217	1531	905	1,69	1896	2312	2759	3244	2,3	5/8	3/8	275	5/31°	1	640	36,5	481	409	324	DWG28	3	12	UNJ6226ZX	

Note:
Expansion device C/V
Expansion device C: UEMT37HDP, UEMT50HDP
UD - Under Development

High efficiency versions of UNEK models (UNEU) available on demand

R404A / R507 / R452A - LBP • 50Hz

							PERFORMANCE DATA ASHRAE				PERFORMANCE DATA EN13215																								
SERIES	MODEL	VOLTAGE & FREQUENCY CODE	MOTOR TYPE	DISPL: cm³	LRA A	HP	EVAPORATING TEMPERATURE °C														RECEIVER VOLUME LITER	VALVE CONNECTION EXTERNAL DIAMETER		FAN				WEIGHT (REFERENCE ONLY) kg	OVERALL DIMENSIONS				CONDENSER		MODEL
							RATED POINT -23,3 °C				-40 W	RATED POINT -35 °C			-30 W	-25 W	-20 W		-15 W	-10 W		SUCTION inch	LIQUID inch	EXTERNAL DIAMETER mm	NO. / ANGLE OF BLADES	NO. OF FANS	AIR FLOW RATE m³/h		A mm	B mm	C mm	EXT. VIEW REF.	NO. OF ROWS	NO. OF TUBES	
							COOLING W	POWER INPUT W	CURRENT A	EFFICIENCY W/W		COOLING W	POWER INPUT W	EFFICIENCY W/W																					
UEMT	UEMT2117GK	A	CSIR	4,50	7,7	1/4	UD	UD	UD	UD	UD	145	144	1,01	UD	UD	UD		UD	UD	0,6	3/8	1/4	200	5/28°	1	300	17,1	430	308	226	DWG02	3	8	UEMT2117GK
	UEMT2121GK	A	CSIR	5,20	8,5	1/4+	327	222	1,46	1,47	308	183	175	1,05	229	286	354		431	519	0,6	3/8	1/4	200	5/28°	1	300	18,2	430	308	226	DWG02	3	8	UEMT2121GK
	UEMT2125GK	A	CSIR	5,96	9,8	1/2-	362	265	1,72	1,37	156	203	213	0,95	257	317	384		458	538	1,1	3/8	1/4	230	5/31°	1	420	15,4	435 / 17,13	308 / 12,13	254 / 10,00	DWG03	3	9	UEMT2125GK
	UEMT2130GK	A	CSIR	6,76	12,4	1/2	UD	UD	UD	UD	UD	239	240	1,00	UD	UD	UD		UD	UD	1,1	3/8	1/4	230	5/31°	1	420	15,4	435 / 17,13	308 / 12,13	254 / 10,00	DWG03	3	9	UEMT2130GK
UNE	UNEK2125GK	A	CSIR	6,20	12,4	1/2	410	342	2,48	1,20	143	185	205	0,90	236	296	364		441	527	1,1	3/8	1/4	230	5/31°	1	420	17,4	435 / 17,13	306 / 12,05	254 / 10,00	DWG05	3	9	UNEK2125GK
	UNEK2134GK	A	CSIR	8,78	16,1	1/2+	490	342	2,77	1,43	180	216	229	0,94	315	401	476		576	687	1,1	3/8	1/4	254	5/28°	1	595	20,0	465 / 18,31	340 / 13,39	296 / 11,65	DWG08	3	11	UNEK2134GK
																					1,1								465 / 18,31	340 / 13,39	296 / 11,65	DWG06			
	UNEK2150GK	A	CSIR	12,12	19,5	3/4	639	530	3,52	1,21	270	322	340	0,95	392	481	589		725	880	1,1	3/8	1/4	254	5/28°	1	595	21,6	465 / 18,31	340 / 13,39	296 / 11,65	DWG08	3	11	UNEK2150GK
																					1,1								465 / 18,31	340 / 13,39	296 / 11,65	DWG06			
	UNEK2168GK	A	CSIR	14,30	18,5	1+	735	617	3,92	1,19	261	367	384	0,95	484	643	825		994	1153	1,1	3/8	1/4	254	5/28°	1	460	23,8	491 / 19,33	340 / 13,39	296 / 11,65	DWG08	4	11	UNEK2168GK
1,1																					465 / 18,31								340 / 13,39	296 / 11,65	DWG06				
UNEKU2168GK	A	CSIR	14,30	22,0	1+	UD	UD	UD	UD	332	430	460	0,93	547	683	838		1011	1203	1,1	3/8	1/4	254	5/28°	1	460	26,8	465 / 18,31	340 / 13,39	296 / 11,65	DWG06	4	11	UNEKU2168GK	
UNT	UNT2168GK	N	CSR	14,50	25,5	1+	832	655	2,92	1,27	264	367	375	0,98	492	645	810		1013	1246	1,1	3/8	1/4	254	5/28°	1	460	26,8	476 / 18,74	340 / 13,39	296 / 11,65	DWG17	4	11	UNT2168GK
	UNT2178GK	A	CSIR	17,40	25,0	1 1/4-	891	655	4,39	1,36	334	453	458	0,99	587	735	897		1073	1263	1,2	3/8	1/4	254	5/28°	1	460	27,5	476 / 18,74	340 / 13,39	296 / 11,65	DWG17	4	11	UNT2178GK
	UNT2180GK	A	CSIR	20,40	34,5	1 1/4	973	701	4,20	1,39	403	513	535	0,96	653	831	1012		1232	1471	1,2	3/8	1/4	254	5/28°	1	460	28,6	476 / 18,74	340 / 13,39	296 / 11,65	DWG17	4	11	UNT2180GK
	UNT2192GK**	A	CSR	22,40	34,5	1 1/2	1113	842	5,50	1,32	394	523	581	0,90	691	896	1142		1443	1787	2,3	3/8	1/4	275	5/31°	1	800	36,2	470 / 18,50	395 / 15,55	324 / 12,76	DWG15	3	12	UNT2192GK
	UNT2210GK	A	CSR	26,20	33,0	1 3/4-	1258	998	5,20	1,26	524	711	743	0,96	905	1105	1311		1524	1744	2,3	1/2	3/8	275	5/31°	1	800	34,6	470 / 18,50	395 / 15,55	324 / 12,76	DWG15	3	12	UNT2210GK
	UNT2212GK **	A	CSR	27,80	33,0	2-	1443	991	5,25	1,46	636	823	767	1,07	1032	1263	1516		1791	2089	2,3	1/2	3/8	275	5/31°	1	800	34,6	470 / 18,50	395 / 15,55	324 / 12,76	DWG15	3	12	UNT2212GK
UNJ	UNJ2192GK	A	CSR	26,10	26,0	1 1/2	1198	942	4,75	1,27	510	689	734	0,94	888	1107	1345		1604	1882	2,3	1/2	3/8	275	5/31°	1	800	37,8	481 / 18,94	409 / 16,10	324 / 12,76	DWG27	3	12	UNJ2192GK
	UNJ2192GS	M	3 PH	26,10	13,5	1 1/4+	1081	900	2,28	1,20	359	495	533	0,93	657	846	1063		1320	1605	2,3	1/2	3/8	275	5/31°	1	800	36,2	481 / 18,94	409 / 16,10	324 / 12,76	DWG28	3	12	UNJ2192GS
	UNJ2212GK	A	CSR	34,40	36,0	2	1599	1175	6,05	1,36	488	717	745	0,96	962	1251	1574		1950	2366	2,3	5/8	3/8	275	5/31°	1	800	39,0	481 / 18,94	409 / 16,10	324 / 12,76	DWG27	3	12	UNJ2212GK
	UNJ2212GS	M	3 PH	34,40	20,6	2+	1599	1479	2,38	1,08	654	902	770	1,17	1151	1402	1654		1909	2165	2,3	5/8	3/8	275	5/31°	1	800	38,2	481 / 18,94	409 / 16,10	324 / 12,76	DWG28	3	12	UNJ2212GS

UNT2192GK**	A	CSR	22,4	34,5	1 1/2		842	5,5	394		523	581	0,90	0	896	1142		1142	1787	2,3	3/8	1/4	275	5/31°	1	800	36,2	470 / 18.50	395 / 15,55	324 / 12,76	1955401	3	12	UNT2192GK**
		CSIR		35		1113																						476 / 18.74	400 / 15,75	324 / 12,76	1955413			

Note:
Expansion device C/V
UD - Under Development
** Available also in CSIR execution and assembly group DWG17

High efficiency versions of UNEK models (UNEU) available on demand

R404A / R507 / R452A - M/HBP • 50Hz

							PERFORMANCE DATA ASHRAE				PERFORMANCE DATA EN13215																										
SERIES	MODEL	VOLTAGE & FREQUENCY CODE	MOTOR TYPE	DISPL. cm³	LRA A	HP	EVAPORATING TEMPERATURE °C																RECEIVER VOLUME liter	VALVE CONNECTION EXTERNAL DIAMETER		FAN				WEIGHT (REFERENCE ONLY) kg	OVERALL DIMENSIONS				CONDENSER		MODEL
							RATED POINT 7,2 °C				-20 W	-15 W	RATED POINT -10 °C			-5 W	0 W	5 W	10 W	SUCTION inch	LIQUID inch	EXTERNAL DIAMETER mm		NO. / ANGLE OF BLADES	NO. OF FANS	AIR FLOW RATE m³/h	A mm	B mm	C mm		EXT. VIEW REF.	NO. OF ROWS	NO. OF TUBES				
							COOLING W	POWER INPUT W	CURRENT A	EFFICIENCY W/W			COOLING W	POWER INPUT W	EFFICIENCY W/W																						
UEMT	UEMT6144GK	A	CSIR	3,97	7,7	1/5	649	296	1,68	2,19	266	323	385	222	1,73	452		519	599	680	0,6	3/8	1/4	200	5/28°	1	300	17,1	430	308	226	DWG02	3	8	UEMT6144GK		
	UEMT6152GK	A	CSIR	4,50	8,5	1/4	676	581	1,94	1,16	259	326	395	225	1,76	470		549	631	716	0,6	3/8	1/4	200	5/28°	1	300	13,3	430	308	226	DWG02	3	8	UEMT6152GK		
	UEMT6165GK	A	CSIR	5,20	10,4	1/4	858	407	2,32	2,11	310	395	477	266	1,79	583		697	799	908	1,1	3/8	1/4	200	5/28°	1	420	16,5	435	308	254	DWG03	3	9	UEMT6165GK		
UNE	UNEK6165GK	A	CSIR	6,20	12,4	1/3	UD	UD	UD	UD	350	410	500	319	1,57	628		754	923	1065	1,1	3/8	1/4	200	5/28°	1	420	16,5	435	308	254	DWG05	3	9	UNEK6165GK		
	UNEK6181GK	A	CSIR	7,28	12,0	1/2-	1252	620	2,70	2,02	368	470	585	395	1,48	715		860	1020	1130	1,1	3/8	1/4	254	5/28°	1	595	21,0	467	339	296	DWG08	3	11	UNEK6181GK		
	UNEK6210GK	A	CSIR	8,78	16,1	1/2	1302	628	3,91	2,07	501	611	731	489	1,49	859		995	1140	1294	1,1	3/8	1/4	254	5/28°	1	595	21,4	467	339	296	DWG08	3	11	UNEK6210GK		
	UNEK6213GK	A	CSIR	12,12	19,3	1/2+	1531	1074	5,97	1,43	633	802	966	634	1,52	1130		1292	1480	1730	1,1	3/8	1/4	254	5/28°	1	595	22,6	467	339	296	DWG08	3	11	UNEK6213GK		
	UNEK6213GK	A	CSR	12,12	14,1	1/2+	1502	843	3,92	1,78	UD	UD	UD	UD	UD	UD		UD	UD	UD	1,1	3/8	1/4	254	5/28°	1	595	22,6	467	339	296	DWG08	3	11	UNEK6213GK		
UNEK6217GK	A	CSR	14,30	21,5	3/4	1946	799	4,10	2,44	827	1010	1205	734	1,64	1412		1630	1859	2100	2,3	1/2	3/8	275	5/31°	1	640	28,5	470	395	324	DWG09	3	12	UNEK6217GK			
UNEU6210GK	A	CSIR	7,28	16,0	UD	UD	UD	UD	UD	469	565	675	416	1,62	798		933	1082	1244	1,1	3/8	1/4	254	5/28°	1	595		465	340	296	UD	3	11	UNEU6210GK			
UNT	UNT6217GK	A	CSIR	12,55	23,0	3/4	1912	882	5,30	2,17	697	873	1063	630	1,69	1268		1487	1720	1968	2,3	1/2	3/8	275	5/31°	1	640	31,8	470	395	324	DWG09	3	12	UNT6217GK		
	UNT6220GK **	N	CSR	14,50	29,5	3/4+	2124	1095	5,15	1,94	830	1046	1269	715	1,77	1495		1733	1975	2223	2,3	1/2	3/8	275	5/31°	1	640	35,1	470	395	324	DWG15	3	12	UNT6220GK		
	UNT6222GK **	A	CSR	17,40	30,0	1-	2389	1225	6,25	1,95	989	1221	1468	867	1,69	1729		2006	2297	2603	2,3	1/2	3/8	275	5/31°	1	640	31,3	470	395	324	DWG15	3	12	UNT6222GK		
	UNT6224GK	A	CSR	20,40	29,0	1	UD	UD	UD	UD	1032	1296	1636	944	1,73	2009		2444	2950	3428	2,3	1/2	3/8	275	5/31°	1	640	31,3	470	395	324	DWG15	3	12	UNT6224GK		
	UNT6226GK **	A	CSR	22,40	38,0	1+	3016	1500	7,27	2,01	1091	1391	1706	1076	1,59	2048		2414	2808	3210	2,3	1/2	3/8	300	5/28°	1	700	36,4	485	405	372	DWG16	3	14	UNT6226GK		
UNJ	UNJ9226GK	V	CSR	21,70	27,5	1+	3141	1403	6,70	2,24	1047	1364	1701	1035	1,64	2071		2473	2909	3360	2,3	5/8	3/8	300	5/28°	1	700	39,2	512	410	372	DWG29	3	14	UNJ9226GK		
	UNJ9226GS	M	3 PH	21,70	10,0	1	2720	1300	2,78	2,09	883	1107	1339	950	1,41	1580		1831	2091	2360	2,3	5/8	3/8	300	5/28°	1	700	36,9	512	410	372	DWG28	3	14	UNJ9226GS		
	UNJ9232GK	A	CSR	26,10	43,0	1 1/4	3474	1728	8,12	2,01	1340	1656	1995	1040	1,92	2357		2742	3149	3579	3,9	5/8	1/2	300	***	1	1450	46,1	600	440	372	DWG30	3	14	UNJ9232GK		
	UNJ9232GS	M	3 PH	26,10	13,0	1 1/4	3365	1685	3,35	2,00	1265	1646	2015	1256	1,60	2376		2751	3124	3523	3,9	5/8	1/2	300	***	1	1450	43,8	600	440	372	DWG31	3	14	UNJ9232GS		
	UNJ9238GK	V	CSR	32,70	43,0	1 1/2+	4104	2221	10,01	1,85	1776	2223	2674	1608	1,66	3099		3509	3903	4282	3,9	5/8	1/2	300	***	1	1300	46,8	600	440	372	DWG30	4	14	UNJ9238GK		
	UNJ9238GS	M	3 PH	32,70	22,0	1 1/2+	4419	2332	4,49	1,89	1889	2232	2623	1171	2,24	3062		3549	4084	4667	3,9	5/8	1/2	300	***	1	1300	42,0	600	440	372	DWG31	4	14	UNJ9238GS		

Note:
Expansion device C/V
** Available also in CSIR execution and asseblly group DWG17 (1955413)
UD - Under Development

High efficiency versions of UNEK models (UNEU) available on demand

PERFORMANCE DATA ASHRAE	PERFORMANCE DATA EN13215
-------------------------	--------------------------

Notes:
Expansion device C/V
Fan is according EN60335-2-89 and EN 60079-15

PERFORMANCE DATA ASHRAE	PERFORMANCE DATA EN13215
-------------------------	--------------------------

Notes:
Expansion device C/V
Fan is according EN60335-2-89 and EN 60079-15

R134a - LBP • 60Hz

							PERFORMANCE DATA ASHRAE																								
SERIES	MODEL	VOLTAGE & FREQUENCY CODE	MOTOR TYPE	DISPL. cm³	LRA A	HP	EVAPORATING TEMPERATURE °C									RECEIVER VOLUME liter	VALVE CONNECTION EXTERNAL DIAMETER		FAN				WEIGHT (REFERENCE ONLY) kg	OVERALL DIMENSIONS				CONDENSER		MODEL	
							-15 W	-10 W	-5 W	0 W	RATED POINT 7,2 °C						10 W	SUCTION inch	LIQUID inch	EXTERNAL DIAMETER mm	NO. / ANGLE OF BLADES	NO. OF FANS		AIR FLOW RATE m³/h	A mm	B mm	C mm	EXT. VIEW REF.	NO. OF ROWS		NO. OF TUBES
											COOLING W	POWER INPUT W	CURRENT A	EFFICIENCY W/W																	
UNE	UNEU2140Z	G	CSIR	16,80	40,0	1/2	816	1014	1236	1482	1877	940	9,8	2,00	2044		1,0	3/8	1/4	254 / 10,00	5/28°	1	660	17 / 37,5	467 / 18,39	339 / 13,35	296 / 11,65	DWG08	3	11	UNEU2140Z

R134a - HBP • 60Hz

							PERFORMANCE DATA ASHRAE																								
SERIES	MODEL	VOLTAGE & FREQUENCY CODE	MOTOR TYPE	DISPL. cm³	LRA A	HP	EVAPORATING TEMPERATURE °C									RECEIVER VOLUME LITER	VALVE CONNECTION EXTERNAL DIAMETER		FAN				WEIGHT (REFERENCE ONLY) kg	OVERALL DIMENSIONS				CONDENSER		MODEL	
							-15 W	-10 W	-5 W	0 W	RATED POINT 7,2 °C						10 W	SUCTION INCH	LIQUID INCH	EXTERNAL DIAMETER mm	NO. / ANGLE OF BLADES	NO. OF FANS		AIR FLOW RATE m³/h	A mm	B mm	C mm	EXT. VIEW REF.	NO. OF ROWS		NO. OF TUBES
											COOLING W	POWER INPUT W	CURRENT A	EFFICIENCY W/W																	
UNE	UNE6187Z	D	CSIR	12,12	17,3	1/3+	571	717	878	1051	1231	577	3,21	2,13	1429		1,0	3/8	1/4	254 / 10,00	5/28°	1	660	16,0 / 35,6	467 / 18,39	339 / 13,35	296 / 11,65	DWG08	3	11	UNE6187Z
	UNE6187Z	G	CSIR	12,12	29,0	1/3+	571	717	878	1051	1231	577	6,81	2,13	1429		1,0	3/8	1/4	254 / 10,00	5/28°	1	660	20,6 / 45,3	467 / 18,39	339 / 13,35	296 / 11,65	DWG08	3	11	UNE6187Z
	UNEK6160Z	G	CSIR	7,28	13,5	1/4+	369	464	571	692	888	383	4,83	2,32	971		1,0	3/8	1/4	230 / 9,06	5/31°	1	480	16,9 / 37,3	435 / 17,13	306 / 12,05	254 / 10,00	DWG05	3	9	UNEK6160Z
	UNEK6170Z	G	CSIR	8,40	28,5	1/4	431	453	557	683	767	382	5,31	2,01	1121		1,0	3/8	1/4	230 / 9,06	5/31°	1	480	17,4 / 38,7	435 / 17,13	306 / 12,05	254 / 10,00	DWG05	3	9	UNEK6170Z
	UNEK6210Z	G	CSIR	12,12	37,0	1/3+	578	723	884	1061	1342	622	7,3	2,16	1460		1,0	3/8	1/4	254 / 10,00	5/28°	1	660	21,7 / 48,3	467 / 18,39	339 / 13,35	296 / 11,65	DWG08	3	11	UNEK6210Z
	UNEK6212Z	G	CSIR	14,30	40,0	1/2	UD	UD	UD	UD	1574	UD	UD	UD	UD		1,0	3/8	1/4	254 / 10,00	5/28°	1	660	20,0 / 44,0	467 / 18,39	339 / 13,35	296 / 11,65	DWG08	3	11	UNEK6212Z
	UNEK6212Z	B	CSR	14,30	22,5	1/2	UD	UD	UD	UD	1574	UD	UD	UD	UD		1,0	3/8	1/4	254 / 10,00	5/28°	1	660	23,0 / 51,2	467 / 18,39	339 / 13,35	296 / 11,65	DWG08	3	11	UNEK6212Z
	UNEK6214Z	D	CSIR	16,80	30,0	1/2+	UD	UD	UD	UD	1769	UD	UD	UD	UD		1,3	3/8	1/4	254 / 10,00	5/28°	1	660	21,4 / 51,2	467 / 18,39	339 / 13,35	296 / 11,65	DWG08	3	11	UNEK6214Z
	UNEK6214Z	G	CSIR	16,80	48,0	1/2+	UD	UD	UD	UD	1769	UD	UD	UD	UD		1,3	3/8	1/4	254 / 10,00	5/28°	1	660	22,3 / 49,1	467 / 18,39	339 / 13,35	296 / 11,65	DWG08	3	11	UNEK6214Z
	UNEU6187Z	G	CSIR	10,00	39	1/2-	537	669	807	949	1165	532	6,40	2,19	1252		1,0	3/8	1/4	254 / 10,00	5/28°	1	660	20,0 / 44,1	467 / 18,39	339 / 13,35	296 / 11,65	DWG08	3	11	UNEU6187Z
	UNEU6212Z	G	CSIR	14,30	40	1/2	673	830	1009	1211	1543	788	9,14	1,96	1684		1,0	3/8	1/4	254 / 10,00	5/28°	1	660	20,6 / 45,3	467 / 18,39	339 / 13,35	296 / 11,65	DWG08	3	11	UNEU6212Z
	UNEU6214Z	G	CSIR	16,80	50	3/4-	812	992	1190	1404	1742	943	10,18	1,85	1883		1,0	3/8	1/4	254 / 10,00	5/28°	1	660	21,4 / 51,2	467 / 18,39	339 / 13,35	296 / 11,65	DWG08	3	11	UNEU6214Z
UNEU6214Z	D	CSIR	16,80	30	3/4-	812	992	1190	1404	1742	925	5,50	1,88	1883		1,0	3/8	1/4	254 / 10,00	5/28°	1	660	22,3 / 49,1	467 / 18,39	339 / 13,35	296 / 11,65	DWG08	3	11	UNEU6214Z	
UNT	UNT6215Z	D	CSIR	17,40	20,8	1/2+	842	1051	1284	1531	1793	847	5,23	2,12	2075		1,3	3/8	1/4	254 / 10,00	5/28°	1	660	27,2 / 60,0	465 / 18,31	340 / 13,39	296 / 11,65	DWG14	3	11	UNT6215Z
	UNT6215Z	G	CSIR	17,40	44,0	1/2+	852	1064	1293	1540	1805	776	8,69	2,33	2088		1,3	3/8	1/4	254 / 10,00	5/28°	1	660	27,2 / 60,0	465 / 18,31	340 / 13,39	296 / 11,65	DWG14	3	11	UNT6215Z
	UNT6217Z	G	CSR	20,40	45,0	3/4	988	1239	1505	1822	2261	1021	11,40	2,21	2503		2,3	1/2	3/8	275 / 10,83	5/31°	1	720	33,5 / 73,9	470 / 18,50	395 / 15,55	324 / 12,76	DWG15	3	12	UNT6217Z
	UNT6217Z	D	CSIR	20,40	31,0	3/4	988	1239	1505	1822	2261	930	5,60	2,43	2503		2,3	1/2	3/8	275 / 10,83	5/31°	1	720	33,5 / 73,9	470 / 18,50	395 / 15,55	324 / 12,76	DWG18	3	12	UNT6217Z
	UNT6220Z	G	CSR	22,40	54,5	1	1138	1436	1766	2129	2710	1107	11,60	2,45	2954		2,3	1/2	3/8	275 / 10,83	5/31°	1	720	34,5 / 76,0	470 / 18,50	395 / 15,55	324 / 12,76	DWG15	3	12	UNT6220Z
	UNT6220Z	D	CSIR	22,40	33,7	1	1138	1436	1766	2129	2710	1085	6,85	2,50	2954		2,3	1/2	3/8	275 / 10,83	5/31°	1	720	34,5 / 76,0	470 / 18,50	395 / 15,55	324 / 12,76	DWG18	3	12	UNT6220Z
UNJ	UNJ6220Z	D	CSIR	26,10	42,0	1	1163	1470	1790	2156	2520	1124	7,18	2,24	2912		2,3	1/2	3/8	275 / 10,83	5/31°	1	720	34,7 / 76,5	481 / 18,94	409 / 16,10	324 / 12,76	DWG27	3	12	UNJ6220Z
	UNJ6220Z	G	CSIR	26,10	72,0	1	1163	1470	1790	2156	2520	1153	12,69	2,19	2912		2,3	1/2	3/8	275 / 10,83	5/31°	1	720	34,7 / 76,5	481 / 18,94	409 / 16,10	324 / 12,76	DWG27	3	12	UNJ6220Z
	UNJ6226Z	D	CSR	34,40	40,0	1+	1390	1740	2100	2466	2840	1344	6,67	2,11	3323		2,3	5/8	3/8	275 / 10,83	5/31°	1	720	37,5 / 82,7	481 / 18,94	409 / 16,10	324 / 12,76	DWG27	3	12	UNJ6226Z

Notes:
Expansion device C/V

High efficiency versions of UNEK models (UNEU) available on demand

R404A / R507 / R452A - LBP • 60Hz

							PERFORMANCE DATA ASHRAE																										
SERIES	MODEL	VOLTAGE & FREQUENCY CODE	MOTOR TYPE	DISPL. cm³	LRA A	HP	EVAPORATING TEMPERATURE °C											RECEIVER VOLUME liter	VALVE CONNECTION EXTERNAL DIAMETER		FAN					WEIGHT (REF-ERENCE ONLY) kg	OVERALL DIMENSIONS				CONDENSER		MODEL
							-40 W	-35 W	-30 W	RATED POINT -23,3 °C				-20 W	-15 W	-10 W			SUCTION INCH	LIQUID INCH	EXTERNAL DIAMETER mm	NO. / ANGLE OF BLADES	NO. OF FANS	AIR FLOW RATE m³/h	A mm		B mm	C mm	EXT. VIEW REF.	NO. OF ROWS	NO. OF TUBES		
										COOLING W	POWER INPUT W	CURRENT A	EFFICIENCY W/W																				
UNE	UNEK2121GK	G	CSIR	5,45	26,5	1/3	152	199	259	359	298	4,70	1,20	415	513	623		1	3/8	1/4	200 / 7,87	5/28°	1	340	16,6 / 36,6	435 / 17,13	306 / 12,05	254 / 10,00	DWG05	3	8	UNEK2121GK	
	UNEK2125GK	G	CSIR	6,20	26,5	1/3+	178	231	295	403	355	5,21	1,14	455	552	659		1	3/8	1/4	230 / 9,06	5/28°	1	420	17,0 / 37,5	435 / 17,13	306 / 12,05	254 / 10,00	DWG05	3	9	UNEK2125GK	
	UNEK2134GK	G	CSIR	8,78	37,5	3/4	254	329	423	581	465	6,30	1,25	672	827	1001		1	3/8	1/4	254 / 10,00	5/28°	1	595	17,9 / 39,5	467 / 18,39	339 / 13,35	296 / 11,65	DWG08	3	11	UNEK2134GK	
	UNEK2134GK	D	CSIR	8,78	20,0	1/2	254	329	423	581	456	3,41	1,27	672	827	1001		1	3/8	1/4	254 / 10,00	5/28°	1	595	17,9 / 39,5	467 / 18,39	339 / 13,35	296 / 11,65	DWG08	3	11	UNEK2134GK	
	UNEK2150GK	G	CSIR	12,12	41,5	1/2+	317	417	540	742	610	7,80	1,22	856	1049	1265		1	3/8	1/4	254 / 10,00	5/28°	1	595	20,0 / 44,1	467 / 18,39	339 / 13,35	296 / 11,65	DWG08	3	11	UNEK2150GK	
	UNEK2150GK	D	CSIR	12,12	20,0	1/2+	317	417	540	742	598	4,22	1,24	856	1049	1265		1	3/8	1/4	254 / 10,00	5/28°	1	595	20,0 / 44,1	467 / 18,39	339 / 13,35	296 / 11,65	DWG08	3	11	UNEK2150GK	
UNT	UNT2168GK	D	CSR	14,50	29,0	1	342	482	648	911	651	4,30	1,40	1058	1303	1573		1	3/8	1/4	254 / 10,00	5/28°	1	595	26,8 / 59,0	477 / 18,80	398 / 15,7	296 / 11,7	DWG21	4	11	UNT2168GK	
	UNT2168GK	G	CSR	14,50	54,5	1	342	482	648	911	633	6,30	1,44	1058	1303	1573		1	3/8	1/4	254 / 10,00	5/28°	1	595	26,8 / 59,0	477 / 18,80	398 / 15,7	296 / 11,7	DWG21	4	11	UNT2168GK	
	UNT2180GK	D	CSR	20,40	40,0	1	461	655	880	1245	840	4,65	1,45	1420	1735	2080		1	3/8	1/4	254 / 10,00	5/28°	1	595	27,5 / 60,6	477 / 18,80	398 / 15,7	296 / 11,7	DWG21	4	11	UNT2180GK	
	UNT2180GK	G	CSR	20,40	66,0	1	461	655	880	1245	857	8,6	1,45	1420	1735	2080		1	3/8	1/4	254 / 10,00	5/28°	1	595	27,5 / 60,6	477 / 18,80	398 / 15,7	296 / 11,7	DWG21	4	11	UNT2180GK	
	UNT2192GK	D	CSR	22,40	40,0	1+	756	825	922	1039	780	3,90	1,33	1086	1333	1507		2,3	3/8	1/4	275 / 10,83	5/31°	1	800	32,1 / 70,6	470 / 18,50	395 / 15,55	324 / 12,76	DWG15	3	12	UNT2192GK	
	UNT2192GK	G	CSIR	22,40	56,0	1+	756	825	922	1039	927	7,21	1,12	1086	1333	1507		2,3	3/8	1/4	275 / 10,83	5/31°	1	800	36,2 / 79,8	470 / 18,50	395 / 15,55	324 / 12,76	DWG15	3	12	UNT2192GK	
	UNT2212GK	G	CSR	27,80	81,0	2 1/4	720	983	1281	1614	1358	13,31	1,19	1981	2382	2818		2,3	1/2	3/8	275 / 10,83	5/31°	1	800	33,8 / 74,5	470 / 18,50	395 / 15,55	324 / 12,76	DWG15	3	12	UNT2212GK	
	UNT2212GK	D	CSR	27,80	45,0	2 1/4	720	983	1281	1614	1090	5,37	1,48	1981	2382	2818		2,3	1/2	3/8	275 / 10,83	5/31°	1	980	34,7 / 76,5	470 / 18,50	395 / 15,55	324 / 12,76	DWG15	3	12	UNT2212GK	
UNJ	UNJ2192GK	D	CSR	26,10	40,0	1 1/2+	530	715	930	1170	944	4,58	1,24	1442	1742	2067		2,3	1/2	3/8	275 / 10,83	5/31°	1	720	36,2 / 79,8	481 / 18,94	409 / 16,10	324 / 12,76	DWG27	3	12	UNJ2192GK	
	UNJ2212GK	D	CSR	34,40	46,0	2 1/4+	721	1037	1360	1730	1124	5,31	1,54	2136	2571	3048		2,3	5/8	3/8	275 / 10,83	5/31°	1	720	38,3 / 84,2	481 / 18,94	409 / 16,10	324 / 12,76	DWG27	3	12	UNJ2212GK	

Notes:
Expansion device C/V

High efficiency versions of UNEK models (UNEU) available on demand

R404A / R507 / R452A - M/HBP • 60Hz

							PERFORMANCE DATA ASHRAE																									
SERIES	MODEL	VOLTAGE & FREQUENCY CODE	MOTOR TYPE	DISPL. cm³	LRA A	HP	EVAPORATING TEMPERATURE °C											RECEIVER VOLUME liter	VALVE CONNECTION EXTERNAL DIAMETER		FAN				WEIGHT (REFERENCE ONLY) kg	OVERALL DIMENSIONS				CONDENSER		MODEL
							-20 W	-15 W	-10 W	-5 W	0 W	RATED POINT 7,2 °C				10 W			SUCTION inch	LIQUID inch	EXTERNAL DIAMETER mm	NO. / ANGLE OF BLADES	NO. OF FANS	AIR FLOW RATE m³/h		A mm	B mm	C mm	EXT. VIEW REF.	NO. OF ROWS	NO. OF TUBES	
												COOLING W	POWER INPUT W	CUR-RENT A	EFFICIENCY W/W																	
UNE	UNEK6144GK	G	CSIR	4,52	26,0	1/4	299	366	436	511	592	676	376	4,57	1,80	766		0,5	3/8	1/4	200 / 7,87	5/28°	1	340	17,4 / 38,4	431 / 16,97	306 / 12,05	226 / 8,90	DWG05	3	8	UNEK6144GK
	UNEK6210GK	D	CSIR	8,78	23,0	1/3+	470	557	663	786	928	1087	679	4,21	1,60	1265		1,3	3/8	1/4	254 / 10,00	5/28°	1	595	22,7 / 49,9	465 / 18,31	340 / 13,39	296 / 11,65	DWG08	3	11	UNEK6210GK
	UNEK6210GK	G	CSIR	8,78	38,0	1/3+	470	557	663	786	928	1087	642	7,23	1,69	1265		1,3	3/8	1/4	254 / 10,00	5/28°	1	595	22,7 / 49,9	465 / 18,31	340 / 13,39	296 / 11,65	DWG08	3	11	UNEK6210GK
	UNEK6213GK	D	CSIR	12,12	30,0	1/2+	626	785	945	1106	1267	1430	917	5,77	1,56	1756		1,3	3/8	1/4	254 / 10,00	5/28°	1	595	22,3 / 49,0	465 / 18,19	340 / 13,39	296 / 11,65	DWG08	3	11	UNEK6213GK
	UNEK6213GK	G	CSIR	12,12	51,0	1/2+	626	785	945	1106	1267	1430	972	11,42	1,47	1756		1,3	3/8	1/4	254 / 10,00	5/28°	1	595	20,8 / 45,8	465 / 18,19	340 / 13,39	296 / 11,65	DWG08	3	11	UNEK6213GK
UNT	UNT6217GK	D	CSIR	12,60	27,0	3/4	871	1091	1329	1584	1858	2284	798	4,20	2,86	2460		2,3	1/2	3/8	275 / 10,83	5/31°	1	640	30,0 / 66,1	470 / 18,50	395 / 15,55	324 / 12,76	DWG18	3	12	UNT6217GK
	UNT6217GK	G	CSIR	12,60	50,0	3/4	871	1091	1329	1584	1858	2284	814	7,77	2,81	2460		2,3	1/2	3/8	275 / 10,83	5/31°	1	640	30,0 / 66,1	470 / 18,50	395 / 15,55	324 / 12,76	DWG18	3	12	UNT6217GK
	UNT6220GK	D	CSR	14,50	26,5	3/4	1038	1308	1586	1872	2166	2604	1177	5,82	2,21	2779		2,3	1/2	3/8	275 / 10,83	5/31°	1	640	31,0 / 68,2	470 / 18,50	395 / 15,55	324 / 12,76	DWG15	3	12	UNT6220GK
	UNT6220GK	G	CSIR	14,50	54,5	3/4	1038	1308	1586	1872	2166	2604	1200	10,59	2,17	2779		2,3	1/2	3/8	275 / 10,83	5/31°	1	640	31,0 / 68,2	470 / 18,50	395 / 15,55	324 / 12,76	DWG18	3	12	UNT6220GK
	UNT6222GK	D	CSR	17,40	33,7	1	1236	1526	1834	2161	2507	3037	1428	8,65	2,13	3253		2,3	1/2	3/8	275 / 10,83	5/31°	1	640	33,5 / 73,9	470 / 18,50	395 / 15,55	324 / 12,76	DWG15	3	12	UNT6222GK
	UNT6222GK	G	CSR	17,40	70,0	1	1236	1526	1834	2161	2507	3037	1457	16,00	2,13	3253		2,3	1/2	3/8	275 / 10,83	5/31°	1	640	33,5 / 73,9	470 / 18,50	395 / 15,55	324 / 12,76	DWG15	3	12	UNT6222GK
UNJ	UNJ9226GK	D	CSR	21,70	37,0	1+	1522	1745	2077	2338	2890	3508	1611	7,82	2,18	4194		2,3	5/8	3/8	300 / 11,81	5/28°	1	1200	37,5 / 82,7	512 / 20,16	410 / 16,14	390 / 15,35	DWG22	4	14	UNJ9226GK

R290 • MBP • 60Hz

							PERFORMANCE DATA ASHRAE				PERFORMANCE DATA EN13215																								
SERIES	MODEL	VOLTAGE & FREQUENCY CODE	MOTOR TYPE	DISPL. cm³	LRA A	HP	EVAPORATING TEMPERATURE °C										RECEIVER VOLUME liter	VALVE CONNECTION EXTERNAL DIAMETER		FAN				WEIGHT (REFERENCE ONLY) kg	OVERALL DIMENSIONS				CONDENSER		MODEL				
							RATED POINT 7,2 °C				-20 W	-15 W	RATED POINT -10 °C			-5 W		0 W	5 W	10 W	SUCTION inch	LIQUID inch	EXTERNAL DIAMETER mm		NO. / ANGLE OF BLADES	NO. OF FANS	AIR FLOW RATE m³/h	A mm	B mm	C mm		EXT. VIEW REF.	NO. OF ROWS	NO. OF TUBES	
							COOLING W	POWER INPUT W	CURRENT A	EFFICIENCY W/W			COOLING W	POWER INPUT W	EFFICIENCY W/W																				
UNE	UNEK6152U	G	CSIR	5,45	25	1/4	903	350	4,46	2,58	329	416	507	279	1,82		602	702	805	913	1,0	3/8	1/4	230	5/28°	1	420	17,1	435	305	254	DWG05	3	9	UNEK6152U
	UNEU6181U	G	CSIR	7,28	30	1/3	1269	434	4,79	2,92	497	591	701	342	2,05		827	968	1124	1296	1,0	3/8	1/4	254	5/28°	1	595	23,8	465	340	296	DWG08	3	11	UNEU6181U

Notes:
Expansion device C/V
High efficiency versions of UNEK models (UNEU) available on demand

DOUBLE FAN R404A

R404A / R507 / R452A - LBP • 50Hz

							PERFORMANCE DATA ASHRAE				PERFORMANCE DATA EN13215																								
SERIES	MODEL	VOLTAGE & FREQUENCY CODE	MOTOR TYPE	DISPL. cm³	LRA A	HP	EVAPORATING TEMPERATURE °C														RECEIVER VOLUME liter	VALVE CONNECTION EXTERNAL DIAMETER		FAN				WEIGHT (REF. ONLY) kg	OVERALL DIMENSIONS				CONDENSER		MODEL
							RATED POINT -23,3 °C				-40 W	RATED POINT -35 °C			-30 W	-25 W	-20 W	-15 W	-10 W	SUCTION inch		LIQUID inch	EXTERNAL DIAMETER mm	NO. / ANGLE OF BLADES	NO. OF FANS	AIR FLOW RATE m³/h	A mm		B mm	C mm	EXT. VIEW REF.	NO. OF ROWS	NO. OF TUBES		
							COOLING W	POWER INPUT W	CURRENT A	EFFICIENCY W/W		COOLING W	POWER INPUT W	EFFICIENCY W/W																					
UNT	ULNT2212GK	A	CSR	27,8	33	2-	1443	991	5,84	1,46	515	669	710	0,94	873	1130	1438	1820		2258	2,3	1/2	3/8	2X254	5/28°	2	1190	40,0	600	440	321	DWG20	3	11	ULNT2212GK
UNJ	ULNJ2212GK	A	CSR	34,4	36	2	1599	1175	6,14	1,36	488	717	745	0,96	962	1251	1574	1950		2366	2,3	5/8	3/8	2X254	5/28°	2	1190	40,0	612	440	296	DWG25	3	11	ULNJ2212GK

R404A / R507 / R452A - M/HBP • 50Hz

							PERFORMANCE DATA ASHRAE				PERFORMANCE DATA EN13215																										
SERIES	MODEL	VOLTAGE & FREQUENCY CODE	MOTOR TYPE	DISPL. cm³	LRA A	HP	EVAPORATING TEMPERATURE °C														RECEIVER VOLUME liter	VALVE CONNECTION EXTERNAL DIAMETER		FAN				WEIGHT (REF. ONLY) kg	OVERALL DIMENSIONS				CONDENSER		MODEL		
							RATED POINT 7,2 °C				-20 W	-15 W	RATED POINT -10 °C			-5 W	0 W	5 W	10 W	SUCTION inch		LIQUID inch	EXTERNAL DIAMETER mm	NO. / ANGLE OF BLADES	NO. OF FANS	AIR FLOW RATE m³/h	A mm		B mm	C mm	EXT.VIEW REF.	NO. OF ROWS	NO. OF TUBES				
							COOLING W	POWER INPUT W	CURRENT A	EFFICIENCY W/W			COOL-ING W	POWER INPUT W	EFFICIENCY W/W																						
UNT	ULNT6226GK	A	CSR	22,4	38	1+	3016	1500	8,17	2,01	1091	1391	1706	1076	1,59	2048	2414	2808		3210	2,3	1/2	3/8	2X254	5/28°	2	1190	38,6	600	440	296	DWG20	3	11	ULNT6226GK		
UNJ	ULNJ9226GK	V	CSR	21,7	27,5	1+	3141	1403	6,79	2,24	1047	1364	1701	1035	1,64	2071	2473	2909		3360	2,3	5/8	3/8	2X254	5/28°	2	1190	39,7	612	440	296	DWG25	3	11	ULNJ9226GK		
	ULNJ9226GS	M	3 PH	21,7	10	1	2720	1300	3,9	2,09	1040	1351	1655	950	1,74	1951	2259	2565		2831	2,3	5/8	3/8	2X254	5/28°	2	1400	43	785	490	296	DWG24	4	11	ULNJ9226GS		
	ULNJ9232GK	A	CSR	26,1	43	1 1/4	3474	1719	8,38	2,02	1214	1565	1929	1040	1,85	2341	2770	3229		3696	2,3	5/8	1/2	2X254	5/28°	2	850	43,3	785	440	296	DWG23	3	11	ULNJ9232GK		
	ULNJ9232GS	M	3 PH	26,1	13	1 1/4	3365	1709	4,4	1,97	1265	1646	2015	1256	1,60	2376	2751	3124		3523	2,3	5/8	1/2	2X254	5/28°	2	1400	44	785	490	296	DWG24	3	11	ULNJ9232GS		
	ULNJ9238GK	V	CSR	32,7	43	1 1/2+	4104	2221	11,19	1,85	1507	1905	2325	1608	1,45	2942	3282	3819		4372	2,3	5/8	1/2	2X254	5/28°	2	1140	45	785	460	296	DWG23	4	11	ULNJ9238GK		
	ULNJ9238GS	M	3 PH	32,7	22	1 1/2+	4231	2215	5,48	1,91	1614	2012	2438	1171	2,08	2904	3426	3942		4487	2,3	5/8	1/2	2X254	5/28°	2	1600	45,4	785	490	296	DWG24	4	11	ULNJ9238GS		

R404A / R507 / R452A - M/HBP • 60Hz

							PERFORMANCE DATA ASHRAE																									
SERIES	MODEL	VOLTAGE & FREQ. CODE	MOTOR TYPE	DISPL. cm³	LRA A	HP	EVAPORATING TEMPERATURE °C										RECEIVER VOLUME liter		VALVE CONNECTION EXTERNAL DIAMETER		FAN				WEIGHT (REF. ONLY) kg	OVERALL DIMENSIONS				CONDENSER		MODEL
							-20 W	-15 W	-10 W	-5 W	0 W	RATED POINT 7,2 °C				10 W			SUCTION inch	LIQUID inch	EXTERNAL DIAMETER mm	NO. / ANGLE OF BLADES	NO. OF FANS	AIR FLOW RATE m³/h		A mm	B mm	C mm	EXT. VIEW REF.	NO. OF ROWS	NO. OF TUBES	
												COOLING W	POWER INPUT W	CURRENT A	EFFICIENCY W/W																	
UNJ	UNJ9226GK	D	CSR	21,7	37	1+	1522	1745	2077	2338	2890	3508	1611	7,82	2,18	4194	2,3		5/8	3/8	2X254/10,00	5/28°	2	850	39,1 / 76,5	614	440	320	DWG26	3	11	ULNJ9226GK

Notes:
Expansion device C/V

GEMINI UNITS

R134a • M/HBP • 50Hz

							PERFORMANCE DATA ASHRAE				PERFORMANCE DATA EN13215																										
SERIES	MODEL	VOLT. & FREQ. CODE	MOTOR TYPE	DISPL. cm³	LRA A	HP	EVAPORATING TEMPERATURE °C												REC. VOL. liter	VALVE CONNECTION EXTERNAL DIAMETER		FAN				FAN MOTOR			WEIGHT (REF. ONLY) kg	OVERALL DIMENSIONS				CONDENSER		MODEL	
							RATED POINT 7.2 °C				-20 W	-15 W	RATED POINT -10 °C			-5 W	0 W	5 W		10 W	SUCTION inch	LIQUID inch	EXTERNAL DIAMETER mm	NO. / ANGLE OF BLADES	NO. OF FANS	AIR FLOW RATE m³/h	RATED OUTPUT W	RATED INPUT W		RATED INPUT A	A mm	B mm	C mm	EXT. VIEW REF.	NO. OF ROWS		NO. OF TUBES
							COOLING W	POWER INPUT W	CURRENT A	EFFICIENCY W/W			COOLING W	POWER INPUT W	EFFICIENCY W/W																						
UGNJ	UGNJ6220ZX	M	3 PH	2X26,10	2X10,0	1 1/2	4570	2008	3,2	2,28	-	1565	2072	1297	1,60	2655	3366	4141	4976	2,3	1/2	3/8	250	7	2	3020	-	2X100	2X0,2	84	1093	551	311	DWG34	4	11	UGNJ6220ZX
	UGNJ6226ZX	M	3 PH	2X34,40	2X13,0	2	6012	2586	4,6	2,32	-	2160	2781	1780	1,56	3533	4419	5409	6488	2,3	1/2	3/8	250	7	2	3020	-	2X100	2X0,2	84	1093	551	311	DWG34	4	11	UGNJ6226ZX

R404A / R507 / R452A • LBP • 50Hz

							PERFORMANCE DATA ASHRAE				PERFORMANCE DATA EN13215																											
SERIES	MODEL	VOLT. & FREQ. CODE	MOTOR TYPE	DISPL. cm³	LRA A	HP	EVAPORATING TEMPERATURE °C											REC. VOL. liter	VALVE CONNECTION EXTERNAL DIAMETER		FAN				FAN MOTOR			WEIGHT (REF. ONLY) kg	OVERALL DIMENSIONS				CONDENSER		MODEL			
							RATED POINT -23,3 °C				-40 W	RATED POINT -35 °C			-30 W	-25 W			-20 W	-15 W	-10 W	SUCTION inch	LIQUID inch	EXTERNAL DIAMETER mm	NO. / ANGLE OF BLADES	NO. OF FANS	AIR FLOW RATE m³/h		RATED OUTPUT W	RATED INPUT W	RATED INPUT A	A mm	B mm	C mm		EXT. VIEW REF.	NO. OF ROWS	NO. OF TUBES
							COOLING W	POWER INPUT W	CURRENT A	EFFICIENCY W/W		COOLING W	POWER INPUT W	EFFICIENCY W/W																								
UGNT	UGNT2180GK	A	CSR	2X20,40	2X34,5	2	2135	1708	7	1,25	713	987	1012	0,98	1318	1682	2164	2768	3446		2,3	1/2	3/8	254	5/28°	2	1325	2X16	2X60	2X0,42	80	850	530	293	DWG36	4	11	UGNT2180GK
UGNJ	UGNJ2192GK	A	CSR	2X26,10	2X26,0	2 1/4	2396	1884	8,62	1,27	718	990	1065	0,93	1315	1839	2367	2993	3687		2,3	1/2	3/8	254	5/28°	2	1325	2X16	2X60	2X0,42	75	1093	551	311	DWG33	4	11	UGNJ2192GK
	UGNJ2192GS	M	3 PH	2X26,10	2X13,5	2 1/4	2162	1800	4,20	1,20	718	990	1088	0,91	1315	1691	2126	2640	3209		2,3	1/2	3/8	254	5/28°	2	1700	2X34	2X100	2X0,38	85	1093	551	311	DWG33	4	11	UGNJ2192GS
	UGNJ2212GK	A	CSR	2X34,40	2X36,0	2 3/4	3198	2350	12,2	1,36	976	1433	1496	0,96	1924	2502	3148	3900	4732		2,3	1/2	3/8	254	5/28°	2	1325	2X16	2X60	2X0,42	82	1093	551	311	DWG33	4	11	UGNJ2212GK
	UGNJ2212GS	M	3 PH	2X34,40	2X20,6	2 3/4	3198	2958	4,60	1,08	1198	1635	1657	0,99	2129	2680	3287	3951	4672		2,3	1/2	3/8	254	5/28°	2	1700	2X34	2X100	2X0,38	80	1093	551	311	DWG33	4	11	UGNJ2212GS

R404A / R507 / R452A • M/HBP • 50Hz

							PERFORMANCE DATA ASHRAE				PERFORMANCE DATA EN13215																										
SERIES	MODEL	VOLT. & FREQ. CODE	MOTOR TYPE	DISPL. cm³	LRA A	HP	EVAPORATING TEMPERATURE °C												REC. VOL. liter	VALVE CONNECTION EXTERNAL DIAMETER		FAN				FAN MOTOR			WEIGHT (REF. ONLY) kg	OVERALL DIMENSIONS				CONDENSER		MODEL	
							RATED POINT 7.2 °C				-20 W	-15 W	RATED POINT -10 °C			-5 W	0 W	5 W		10 W	SUCTION inch	LIQUID inch	EXTERNAL DIAMETER mm	NO. / ANGLE OF BLADES	NO. OF FANS	AIR FLOW RATE m³/h	RATED OUTPUT W	RATED INPUT W		RATED INPUT A	A mm	B mm	C mm	EXT. VIEW REF.	NO. OF ROWS		NO. OF TUBES
							COOLING W	POWER INPUT W	CURRENT A	EFFICIENCY W/W			COOLING W	POWER INPUT W	EFFICIENCY W/W																						
UGNJ	UGNJ9226GK	V	CSR	2X21,70	2X38,0	2	6082	2806	12,8	2,17	1974	2420	3053	1830	1,67	3783	4607	5534	6500	2,3	1/2	3/8	250	7	2	3008	-	2X115	2X0,51	82	1093	551	311	DWG34	4	11	UGNJ9226GK
	UGNJ9226GS	M	3 PH	2X21,70	2X10,0	2	5440	2600	7,8	2,09	1793	2397	3005	2115	1,42	3636	4318	5029	5662	2,3	1/2	3/8	250	7	2	3020	-	2X100	2X0,2	72,5	1093	551	311	DWG34	4	11	UGNJ9226GS
	UGNJ9232GK	A	CSR	2X26,10	2X43,0	2 1/2	6722	3438	16,8	1,96	2114	2780	3489	2498	1,40	4287	5169	6144	7138	2,3	1/2	3/8	250	7	3	3595	-	3X115	3X0,51	84	1093	551	311	DWG35	4	11	UGNJ9232GK
	UGNJ9232GS	M	3 PH	2X26,10	2X13,0	2 1/2	6730	3418	5,6	1,97	2180	2920	3660	2460	1,49	4428	5259	6125	8538	2,3	1/2	3/8	250	7	3	3660	-	3X100	3X0,2	81	1093	551	311	DWG35	4	11	UGNJ9232GS
	UGNJ9238GK	V	CSR	2X32,70	2X43,0	3	8208	4442	20,2	1,85	3539	4227	4972	3538	1,41	5771	6626	7537	8502	2,3	1/2	3/8	250	7	3	3595	-	3X115	3X0,51	88	1093	551	311	DWG35	4	11	UGNJ9238GK
	UGNJ9238GS	M	3 PH	2X32,70	2X22,0	3	8332	4370	7,2	1,91	2701	3616	4533	3045	1,49	5482	6512	7657	8538	2,3	1/2	3/8	250	7	3	3595	-	3X115	3X0,51	87	1093	551	311	DWG35	4	11	UGNJ9238GS

Notes:
Expansion device C/V

SLIDING UNIT

R134a • MBP • 50Hz

							PERFORMANCE DATA ASHRAE			PERFORMANCE DATA EN13215																							
SERIES	MODEL	VOLTAGE & FREQUENCY CODE	MOTOR TYPE	DISPL. cm³	LRA A	HP	EVAPORATING TEMPERATURE °C														REC. VOLUME liter	VALVE CONNECTION EXTERNAL DIAMETER		FAN		WEIGHT (REF. ONLY) kg	OVERALL DIMENSIONS				CONDENSER		MODEL
							RATED POINT 7,2 °C			-15 W	RATED POINT -10 °C				-5 W	0 W		5 W	10 W	SUCTION inch		LIQUID inch	EXTERNAL DIAMETER mm	AIR FLOW RATE m³/h	A mm		B mm	C mm	EXT. VIEW REF.	NO. OF ROWS	NO. OF TUBES		
							COOLING W	POWER INPUT W	CURRENT A		COOLING W	POWER INPUT W	CURRENT A	EFFICIENCY W/W																			
UNE	UDNEK6210Z	A	CSIR	12,12	19,5	1/3+	1150	522	3,05	479	597	364	2,55	1,64	729	875		1036	1212	1,1	3/8	1/4	250	840	65	822	460	470	DWG37	3	11	UDNEK6210Z	
	UDNEK6212Z	A	CSIR	14,3	19,5	1/2	1342	652	3,88	545	662	438	3,30	1,51	883	968		1280	1327	1,1	3/8	1/4	250	840	66	822	460	470	DWG37	3	11	UDNEK6212Z	
	UDNEK6214Z	A	CSIR	16,8	21,2	1/2+	1439	776	5,06	610	758	542	4,32	1,40	931	1098		1374	1541	1,1	3/8	1/4	250	840	66	822	460	470	DWG37	3	12	UDNEK6214Z	
UNT	UDNT6215Z	N	CSIR	17,4	21	1/2+	1566	741	4,4	657	820	479	3,30	1,71	1001	1200		1416	1641	2,3	3/8	1/4	250	840	69	822	460	470	DWG37	3	12	UDNT6215Z	
	UDNT6217Z	A	CSR	20,4	25	3/4+	1798	779	5,41	774	956	615	4,53	1,55	1166	1406		1647	1872	2,3	1/2	3/8	250	840	75,5	822	460	470	DWG37	3	12	UDNT6217Z	
UNJ	UDNJ6220Z	A	CSR	26,1	35	1	2312	1083	6,37	963	1226	738	5,23	1,66	1512	1832		2158	2516	2,3	1/2	3/8	250	840	75,5	822	460	470	DWG37	3	12	UDNJ6220Z	
	UDNJ6226Z	A	CSR	34,4	31	1 1/4	2983	1360	6,8	1234	1521	901	6,07	1,69	1835	2177		2547	2944	2,3	1/2	3/8	300	1450	82	822	460	470	DWG37	3	14	UDNJ6226Z	

R404A / R507 / R452A - LBP • 50Hz

							PERFORMANCE DATA ASHRAE			PERFORMANCE DATA EN13215																								
SERIES	MODEL	VOLTAGE & FREQUENCY CODE	MOTOR TYPE	DISPL. cm³	LRA A	HP	EVAPORATING TEMPERATURE °C															REC. VOLUME liter	VALVE CONNECTION EXTERNAL DIAMETER		FAN		WEIGHT (REF. ONLY) kg	OVERALL DIMENSIONS				CONDENSER		MODEL
							RATED POINT -23,3 °C			-40 W	RATED POINT -35 °C				-30 W	-25 W		-20 W	-15 W	-10 W	SUCTION inch		LIQUID inch	EXTERNAL DIAMETER mm	AIR FLOW RATE m³/h	A mm		B mm	C mm	EXT. VIEW REF.	NO. OF ROWS	NO. OF TUBES		
							COOLING W	POWER INPUT W	CURRENT A		COOLING W	POWER INPUT W	CURRENT A	EFFICIENCY W/W																				
UNE	UDNEK2150GK	A	CSIR	12,12	19,5	3/4	535	525	3,6	236	319	386	3,05	0,83	387	497		578	690	830	1,1	3/8	1/4	250	840	65	822	460	470	DWG37	3	11	UDNEK2150GK	
	UDNEK2168GK	A	CSIR	14,3	18,5	1	608	602	4,1	312	386	444	3,5	0,87	497	614		730	841	930	1,1	3/8	1/4	250	840	66	822	460	470	DWG37	3	12	UDNEK2168GK	
UNT	UDNT2180GK	A	CSR	20,4	34,5	1+	809	762	4,7	423	538	575	2,8	0,94	668	813		973	1147	1336	2,3	1/2	3/8	250	840	66	822	460	470	DWG37	3	12	UDNT2180GK	
	UDNT2192GK	A	CSR	22,4	34,5	1 1/2	912	744	3,8	450	607	553	2,9	1,10	773	950		1136	1332	1538	2,3	1/2	3/8	300	1450	75,5	822	460	470	DWG37	3	12	UDNT2192GK	
	UDNT2212GK	A	CSR	27,8	33	2-	1125	955	4,8	556	725	710	3,7	1,02	915	1134		1355	1606	1873	2,3	1/2	3/8	300	1450	75,5	822	460	470	DWG37	3	14	UDNT2212GK	
UNJ	UDNJ2212GK	A	CSR	34,4	36	2	1315	1210	5,9	617	849	848	4,4	1,00	1085	1339		1565	1810	2057	2,3	1/2	3/8	300	1450	76	822	460	470	DWG37	3	14	UDNJ2212GK	
UL	UDL63B752BBK	A	CSR	46	49	2 1/6	2251	1288	7,04	631	947	815	5,28	1,16	1281	1632		2002	2390	2795	4	5/8	3/8	400	2750	116	890	632	599	DWG39	4	18	UDL63B752BBK	
	UDL63A113BBK	A	CSR	65	60	3 1/5	3333	1856	8,82	967	1377	1183	6,21	1,16	1854	2399		3012	3692	4441	4	5/8	3/8	400	2750	116	890	632	599	DWG39	4	18	UDL63A113BBK	
	UDL63A183BBK	A	CSR	99	104	4	4169	2344	12,7	1537	1958	1745	10,66	1,12	2458	3037		3695	4432	5248	4	3/4	1/2	400	2750	116	890	632	599	DWG39	4	18	UDL63A183BBK	

Notes:
Expansion device C/V

R404A / R507 / R452A - M/HBP • 50Hz

Notes:
Expansion device C/V

SUPERTROPICAL

R404A / R507 / R452A - LBP • 50Hz

							PERFORMANCE DATA ASHRAE				PERFORMANCE DATA EN13215																								
SERIES	MODEL	VOLTAGE & FREQUENCY CODE	MOTOR TYPE	DISPL. cm³	LRA A	HP	EVAPORATING TEMPERATURE °C														REC. VOLUME liter	VALVE CONNECTION EXTERNAL DIAMETER		FAN				WEIGHT (REF. ONLY) kg	OVERALL DIMENSIONS				CONDENSER		MODEL
							RATED POINT -23,3 °C				-40 W	RATED POINT -35 °C			-30 W	-25 W	-20 W	-15 W	-0 W	SUCTION inch		LIQUID inch	EXTERNAL DIAMETER mm	NO. / ANGLE OF BLADES	NO. OF FANS	AIR FLOW RATE m³/h	A mm		B mm	C mm	EXT. VIEW REF.	NO. OF ROWS	NO. OF TUBES		
							COOLING W	POWER INPUT W	CURRENT A	EFFICIENCY W/W		COOLING W	POWER INPUT W	EFFICIENCY W/W																					
UNJ	USNJ2192GK	A	CSR	26,1	26,0	1 1/2	1410	1032	5,1	1,37	542	742	785	0,95	945		1.102	1385	1502	1854	2,3	1/2	3/8	275	5/31º	1	1450	38	482	411	372	DWG29	3	14	USNJ2192GK
	USNJ2212GK	A	CSR	34,4	36,0	2	1758	1288	6,3	1,36	573	789	834	0,95	1051		1.423	1726	2156	2597	2,3	5/8	3/8	275	5/31º	1	1450	39	482	411	372	DWG29	3	14	USNJ2212GK

R404A / R507 / R452A - M/HBP • 50Hz

							PERFORMANCE DATA ASHRAE				PERFORMANCE DATA EN13215																								
SERIES	MODEL	VOLTAGE & FREQUENCY CODE	MOTOR TYPE	DISPL. cm³	LRA A	HP	EVAPORATING TEMPERATURE °C														REC. VOLUME liter	VALVE CONNECTION EXTERNAL DIAMETER		FAN				WEIGHT (REF. ONLY) kg	OVERALL DIMENSIONS				CONDENSER		MODEL
							RATED POINT 7,2 °C				-20 W	-15 W	RATED POINT -10 °C			-5 W	0 W	5 W	10 W	SUCTION inch		LIQUID inch	EXTERNAL DIAMETER mm	NO. / ANGLE OF BLADES	NO. OF FANS	AIR FLOW RATE m³/h	A mm		B mm	C mm	EXT. VIEW REF.	NO. OF ROWS	NO. OF TUBES		
							COOLING W	POWER INPUT W	CURRENT A	EFFICIENCY W/W			COOLING W	POWER INPUT W	EFFICIENCY W/W																				
UEMT	USEMT6165GK	A	CSIR	5,20	10,4	1/4	1020	351	2,2	2,91	375	448	530	305	1,74		620	719	840	972	1,1	3/8	1/4	254	5/28°	1	595	17	466	343	296	DWG04	3	11	USEMT6165GK
UNE	USNEK6210GK	A	CSIR	8,78	16,1	1/2	1563	733	4,12	2,13	541	683	792	448	1,77		921	1084	1248	1603	1,1	3/8	1/4	254	5/28°	1	595	22,7	476	399	296	DWG10	3	11	USNEK6210GK
	USNEK6213GK	A	CSIR	12,12	19,3	1/2+	1930	965	5,3	2,00	660	856	1035	675	1,53		1208	1369	1512	1886	1,1	3/8	1/4	275	5/31°	1	1450	24	476	399	324	DWG11	3	12	USNEK6213GK
UNJ	USNJ9226GK	V	CSR	21,7	27,5	1	3436	1540	7,2	2,23	1164	1498	1876	1070	1,75		2282	2684	3384	3693	2,3	5/8	3/8	300	-	1	1450	39	600	440	372	DWG31	3	14	USNJ9226GK
	USNJ9232GK	A	CSR	26,1	43,0	1 1/4	3587	1832	8,6	1,96	1435	1787	2206	1282	1,72		2482	2757	3976	4012	3,9	5/8	1/2	300	-	1	1300	46	600	440	372	DWG31	4	14	USNJ9232GK
	USNJ9238GK	V	CSR	32,7	43,0	1 1/2+	4512	2332	11,2	1,93	1812	2103	2577	1610	1,60		3287	3622	4540	4893	3,9	5/8	1/2	300	-	1	2200	48	600	440	426	DWG32	4	16	USNJ9238GK
	USNJ9238GS	M	CSR	32,7	22,0	1 1/2+	4863	2543	5,3	1,91	1866	2234	2668	1472	1,81		3356	3834	4763	4968	3,9	5/8	1/2	300	-	1	2200	48	600	440	426	DWG32	4	16	USNJ9238GS





Notes:
Expansion device C/V

High efficiency versions of UNEK models (UNEU) available on demand





EXTERNAL VIEWS & WIRING DIAGRAMS







EXTERNAL VIEWS - UEMT




EXTERNAL VIEWS UNE/UNEK/UNEU











EXTERNAL VIEWS UNE/UNEK/UNEU







EXTERNAL VIEWS UNE/UNEK/UNEU







EXTERNAL VIEWS UNT






EXTERNAL VIEWS UNJ







EXTERNAL VIEWS UNJ






EXTERNAL VIEWS UNJ



EXTERNAL VIEWS - UGNJ - UGNT - GEMINI UNITS



EXTERNAL VIEWS SLIDING UNIT



WIRING DIAGRAMS KEY

	OVERLOAD PROTECTOR		COMMON (INTERNAL OVERLOAD PROTECTOR)
	START RELAY		START
	START CAPACITOR		COMMON
	RUN CAPACITOR		RUN
	FAN MOTOR		WHITE CABLE
	THERMOSTAT		BLACK CABLE
	EARTH CONNECTION		YELLOW-GREEN CABLE
	TERMINAL BLOCK		BROWN CABLE
	LAMP		BLUE CABLE
	PUSH BUTTON		RED CABLE
	LOW-HIGH PRESSURE SWITCH		

WIRING DIAGRAMS

SM00 - UEMT SERIE RSIR CORD ANCHORAGE & PTC

SM03 - UNE SERIE RSIR TERMINAL BOARD

SM04 - UNE SERIE CSIR AMERICAN VERSION

WIRING DIAGRAMS



SM05 - UEMT, UNE SERIES CSIR TERMINAL BOARD

SM06 - UNE, UNT SERIES CSR BOX







SM16 - UNJ SERIE - CSR BOX (Internal Overload Protector)

WIRING DIAGRAMS

SM017 - UNJ SERIE CSR BOX (External Overload Protector)





SM18 - UNJ SERIE - 3-PHASE (Internal Overload Protection)





WIRING DIAGRAMS



SM19 - UNT SERIE CSIR TERMINAL BOARD



SM20 - UNT SERIE CSIR AMERICAN VERSION




SM21 - UNT SERIE CSR BOX




WIRING DIAGRAMS


SM26 - NT SERIES CSR BOX (Internal Overload Protector)



SM27 - NT SERIES 3-PHASE (Internal + External Overload Protector)




SM28 - SLIDING UNIT CONNECTION




WIRING DIAGRAMS

SM29 - SLIDING UNIT CSR



SM30 - SLIDING UNIT CSIR WITH FAN SPEED



LOCATIONS



BRAZIL

Rui Barbosa, 1020 - P.O. BOX 91
89219-901 - Joinville - SC - Brazil
Phone: +55 47 3441-2121
Fax: + 55 47 3441-2780



CHINA

29 Yuhua Road
Area B of Beijing Tianzhu Airport industrial Zone
101312 - Beijing - China
Phone: +86 10 8048-2255
Fax: +86 10 6725-6825



ITALY

Via Pietro Andriano, 12
10020 - Riva Presso Chieri (Torino) - Italy
P.O. BOX 151 - 10023 Chieri (TO)
Phone: +39 011 943-7111
Fax: +39 011 946-8377
+39 011 946-9950



EMBRACO MÉXICO

Avenida de las Industrias 501 PIMSA
Oriente Apodaca
Nuevo León - México
Phone: +52 81 4780-6700



RUSSIA

BC Lotos
Office 13 - 5 floor, room III
Odesskaya st., 2 - Moscow 117638 - Russia
Phone: +7 495 640-7050
Fax: +7 495 640-7060
General manager : Mr. Vladimir Demyachenko



SLOVAKIA

Odorinska Cesta, 2 - 052-01
Spišská Nová Ves - Slovakia
Phone: +42 153 417-2291
+42 153 417-2293
Fax: +42 153 417-2299



U.S.A.

1610 Satellite Blvd - Suite B
Duluth, GA 30097
Phone: +1 800 548-9498
Fax: +1 877 631-9016
Tech Support: +1 678 804-1374

embraco POWER IN.
CHANGE ON.



are registered trademarks owned by Whirlpool SA - Embraco Compressors Business Unit and they will continue to be exploited for the Compressors marketing and sale with or without the new trademark EMBRACO.



GLOBAL PRESENCE

CONTACT US:

marketing.europe@embraco.com

SALES OFFICE:

Via Pietro Andriano, 12
10020 – Riva presso Chieri (TO) - Italy